

# Ovation Rêve 3 Wash – Fresnel Lens

An optional Fresnel lens accessory designed to modify the beam of the Ovation Rêve 3 Wash for a classic, soft-edged field of light.

It provides designers with greater flexibility for applications in theatre, broadcast, or corporate events requiring a beautifully even and controlled wash.

- Fully featured moving head Fresnel wash fixture with red, green, blue, cyan, amber and mint full spectrum LEDs with CRI >98. Fixture also features a four-blade internal barn door system with +/- 60° rotation, a zoom, prism, and variable frost
- Fixture can be fitted with either PC or Fresnel lens (PC lens is an accessory)
- Stand out features include the fact that this fixture is only a part of a complete ecosystem within the Ovation family. All moving heads in the Ovation family share the same color attributes so that the colors match across the series.
- Multiple fan modes including OFF allowing this fixture to be used in a multitude of applications
- 22 bit dimming with user selectable red shift of master dimmer for smooth control of fades
- +/- green adjustment for on camera hue correction
- Attachable accessory holder for gel frames, top hats, and the like
- NFC configuration with app
- Battery backup display with auto-rotate depending on fixture orientation
- Ethernet pass through
- True 1 compatible power input/output

## SPECIFICATIONS

### Optical *

**Light Source:** 1 LEDs (RGBCAM) 50,000 hours life expectancy

** These specifications are still being finalized. Speak to a salesperson for more information.*

### Dynamic Effects

**Pan and Tilt:** 540°/270°

**Colors:** Red, Green, Blue, Cyan, Amber, Mint

**Internal Barn Doors:** 4

### Construction / Physical

**Dimensions:** 16.14 x 11.02 x 28.18 in (410 x 280 x 716 mm)

**Weight:** 68.8 lb (31.2 kg)

**IP Rating:** IP20

### Connections

**Power Connection:** Edison plug to Seetronic Powerkon IP65

**Power Input:** Seetronic Powerkon IP65

**Power Output:** Seetronic Powerkon IP65

**Data Connectors:** 5-pin XLR, Amphenol XLR Net RJ45 connectors in/out

### Control

**Control Protocol:** Art-Net, sACN, DMX, CRMX (optional)

### Electrical

**Input Voltage:**

**Power and Current:** 1229 W, 10.26 A @ 120 V, 60 Hz

**Power and Current:** 1194 W, 5.87 A @ 208 V, 60 Hz

**Power and Current:** 1190 W, 5.36 A @ 230 V, 50 Hz

### Certifications / Qualifications

**Compliance:** CE, MET, FCC, CB