

Ovation Rêve H2

Ovation Rêve H2 is a high-performance RGBCAM houselight with exceptional color quality and output, featuring the improved Rêve engine and modernized feature and control sets.

- RGBCAM houselight with exceptional color quality and output
- Improved “Rêve” engine with updated features and look
- Updated and modernized feature and control sets

SPECIFICATIONS

Optical *

Light Source: RGBCAM LED Array. L70 rating: 55,000 hours under LED manufacturers test conditions (LM-80: 10,000hrs)

** These specifications are still being finalized. Speak to a salesperson for more information.*

Dynamic Effects

Colors: VCW and CCT Presets

Construction / Physical

Dimensions: 14 x 8 x 8 in (355.6 x 203.2 x 203.2 mm)

Weight: 16.4 lb (7.5 kg)

IP Rating: IP20

Connections

Power Input: Hard-wired, Seetronic Powerkon IP65, 48v Emergency

Data Connectors: 5-pin XLR, Phoenix connector

Control

Control Protocol: DMX, RDM, CRMX

Electrical

Input Voltage: 100 to 277 VAC, 50/60 Hz (auto-ranging)

Power and Current: 199 W, 1.66 A @ 120 V, 60 Hz

Power and Current: 197 W, 0.96 A @ 208 V, 60 Hz

Power and Current: 196 W, 0.87 A @ 230 V, 50 Hz

Certifications / Qualifications

Compliance: CE, MET, FCC, CB