

# Amhaze Stadium

The Amhaze Stadium is a tour-ready, professional water-based haze machine providing powerful output with a rapid 30-second heat-up time and adjustable control, all housed in a durable road case.

Ideal for large-scale touring, productions, and events that demand a robust, high-output haze effect capable of withstanding the rigors of the road.



- Generates 157 cfm of high-output haze to quickly fill large venues.
- Features an adjustable vent louver for precise, directional control of haze flow.
- Offers highly efficient fluid consumption, running up to 11 hours on one container.
- Provides versatile output and fan speed control via DMX or onboard manual knobs.
- Built for touring with a rugged road case and an M12 threaded rigging insert.
- Includes an automatic low fluid shutdown feature to protect the pump from damage.

## SPECIFICATIONS

### Dynamic Effects

**Fan Speed:** 157 cfm

**Low Fluid Shutdown:** Yes

### Construction / Physical

**Dimensions:** 20.60 in (523.42 mm) x 10.80 in (274.9 mm) x 15.97 (405.7 mm)

**Weight:** 38.4 lb (17.4 kg)

**Threaded Bolt:** M12

**Exterior Color:** Black

**Tank Capacity:** 1.3 gal (4.92l)

**Fluid Consumption:** 9.5 ml/min (0.15 gallons/hour)

**Maximum Run time:** >8.25 hours @ full volume

### Connections

**Power Connection:** Edison (local) plug to Seetronic Powerkon IP65

**Power Input:** Seetronic Powerkon IP65

**Data Connectors:** 3- and 5-pin XLR

**Cable Length (power):** 5 ft (1.5 m)

### Control

**Control Protocol:** DMX

**DMX Channels:** 2

**Modes/Personalities:** 1 personality

**On-Board Control:** Yes

### Electrical

**Input Voltage:** 120 VAC, 50/60 Hz or 230 VAC, 50 Hz

**Power and Current:** 1,230 W, 10.25 A @ 120 V, 50/60 Hz

**Power and Current:** 2,430 W, 10.56 A @ 230 V, 50 Hz

**Heat-up Time:** 30 sec

### Certifications / Qualifications

**Certifications:** CE, MET, RCC, RoHS

**MET Listing Number:** E115095

**US Safety:** UL 499

**Canadian Safety:** CSA C22.2 No. 64-10

**IP Rating:** IP20, dry location

**Minimum distance from flammable material to all exterior surfaces of the product:** 3.3 ft (1 m)

**Maximum exterior surface temperature (Tc):** 127 °F (53 °C)

### Required Accessories

Compatible Mounting Options: M12 Bolt/Clamp  
PHF5L Haze Fluid

### Optional Accessories

Clamps  
Neutrik® powerCON® cables  
DMX Cables

### What's Included

Amhaze Stadium  
Seetronic Powerkon IP65 power cord  
Warranty Card  
Quick Reference Guide or User Manual