

Cloud 9



A high-output, low-lying fogger that creates thick, continuous cloud-like effects using only water and fog fluid, eliminating the need for dry ice or CO₂. Ideal for use on large-scale stages, in theatres, during live performances, and at theme parks requiring powerful, ground-hugging atmospheric effects.

- Produces 15,000 cfm of continuous fog, covering large areas up to 300 m².
- Uses ultrasonic technology to create dense, ground-hugging effects with standard fluids.
- Reaches full operational temperature in just three minutes for rapid deployment.
- Housed within a rugged flight case with locking casters for simplified transport and durability.
- Offers flexible control options via its onboard digital display or standard 2-channel DMX.
- Features an integrated water drain system and low fluid shutdown for reliable operation.

SPECIFICATIONS

Dynamic Effects

Output: 15,000 cfm

Low Fluid Shutdown: Yes

Compatible Fluids:

HDF: Best overall performance for a medium to large coverage area. Fog dissipates after lifting into the air.

PHF: Great dual-purpose effect. Good coverage area. Fog lifts into the air to become haze.

Construction / Physical

Dimensions: 33.85 x 19.29 x 24.80 in (860 x 490 x 630 mm)

Output Nozzle (outer diameter): 4.76 in (121 mm)

Hose Length (fully extended): 8 ft (2.44 m)

Weight: 121.3 lb (55.8 kg)

Exterior Color: Black

Fluid Tank Capacity: 0.92 gal (3.5 l)

Water tank Capacity: 5.3 gal (20 l)

Fluid Consumption: 29 ml/min (0.007 gal/min)

Water Consumption (distilled): 165 ml/min (0.044 gal/min)

Maximum Run Time: 2 hours max runtime @ 100% output

Connections

Power Connection: Edison plug to Seetronic Powerkon IP65

Power Input: Seetronic Powerkon IP65 (2x 120 V, 1x 230 V)

Data Connectors: 3- and 5-pin XLR

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX,

DMX Channels: 2

Modes/Personalities: 1 personalities (2)

On-Board Control: Yes

Electrical

Input Voltage: 120 VAC, 60 Hz or 230 VAC, 50 Hz

Power and Current (input A): 1000 W, 8.36 A @ 120 V, 60 Hz (120 V version)

Power and Current (input B): 1130 W, 9.40 A @ 120 V, 60 Hz (120 V version)

Power and Current: 2,600 W, 11.3 A @ 230 V, 50 Hz (230 V version)

Heat-up Time: 3 min

Breaker Size: 15 A (Input A, 120 V version)

Breaker Size: 20 A (230 V version)

Certifications / Qualifications

Certifications: CE

IP Rating: IP20, dry location

Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

Thermal Dissipation @ 120V: 7,265 BTU per hour (max)

Thermal Dissipation @ 230V: 8,870 BTU per hour (max)

Required Accessories

LLG

Optional Accessories

Neutrik powerCON TRUE1 cables

DMX Cables

What's Included

Cloud 9

2 Seetronic Powerkon IP65

Directional hose and hose clamp

Overflow polyurethane tubing, 8.5 mm, 3ft (0.9 m)