



COLORado 3 Solo

An IP-rated, convection-cooled wash light featuring a fast, smooth zoom and three 60W RGBW LEDs that project an intense and fully homogenized beam. Its silent, weather-resistant design makes it ideal for diverse applications, including quiet theatrical stages and demanding outdoor festival productions.

- Delivers a powerful 15,280 lux output at 5 meters from three 60W RGBW LEDs.
- Offers a versatile and fast zoom range from a narrow 4° to a wide 45°.
- Features adjustable color temperature presets from a warm 3200 K to a cool 10000 K.
- Supports DMX and RDM control with selectable dimming curves for programming versatility.
- Built for all-weather use with IP-rated power and data connectors.
- Allows power linking for up to 15 units for simplified and efficient setup.

SPECIFICATIONS

Optical

Light Source: 3 LEDs (quad-color RGBW) 60 W, (4.4 A), 50,000 hours life expectancy

Beam Angle: 4° to 34°

Field Angle: 8° to 45°

Zoom Range: 4° to 45°

Illuminance (4°): 15,280 lux @ 5 m

Illuminance (34°): 313 lux @ 5 m

Selectable PWM: 600 Hz, 1200 Hz, 2000 Hz, 2400 Hz, 6000 Hz, 25,000 Hz

Dynamic Effects

Dimmer: Electronic

Shutter/Strobe: Electronic

Zoom: Motorized

Strobe Rate: 0 to 25 Hz

Standalone Color Mixing: Yes

Color Temperature Presets: Yes

Dim Modes: 5

Built-in Automated Programs: Yes

Customizable Programs: Yes

Recall Custom Programs: Yes

Construction / Physical

Dimensions: 9.84 x 12.36 x 16.25 in (250 x 314 x 413 mm)

Weight: 19.8 lb (9 kg)

Exterior Color: Black

Housing Material: Magnesium

Accessory Holder/Gel Frame Size: 7.5 in (191 mm)

Connections

Power Connection: Edison (Local) plug to Seetronic Powerkon IP65

Power Input: Seetronic Powerkon IP65

Power Output: Seetronic Powerkon IP65

Data Connectors: 3- and 5-pin IP65 XLR

Cable Length (power): 5 ft (1.5 m)

Control

Protocol(s): DMX, RDM

DMX Channels: 9, 12, or 17

Modes/Personalities: 4 personalities (HSIC, SSP, TOUR, TR16, STD.Y)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 8 units @ 120 V; 14 units @ 208 V; 15 units @ 230 V

Power and Current: 187 W, 1.580 A @ 120 V, 60 Hz

Power and Current: 181 W, 0.909 A @ 208 V, 60 Hz

Power and Current: 175 W, 0.869 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET, FCC

IP Rating: IP65, outdoor/wet, with pressure equalizing M12 GORE® valve

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Neutrik TRUE1 power linking cables

5-pin DMX Cables

Color Blending Filters: DF60X1D

What's Included

COLORado 3 SOLO

Seetronic Powerkon IP65 power cord