



COLORado M Solo

A compact, robust, and silent IP65-rated static wash light featuring RGBW LEDs and a smooth zoom that projects an even, fully homogenized beam. Ideally suited for indoor or outdoor touring and production applications, particularly in tight or noise-sensitive environments.

- Features a powerful 40W RGBW LED source for vibrant color mixing and high output.
- Delivers a versatile zoom range from a tight 4° beam to a broad 24° wash.
- Built with a silent, fan-less convection cooling system for noise-sensitive applications.
- Offers selectable color temperature presets ranging from 3,200 K to 10,000 K.
- Provides flexible DMX control with 9, 12, or 17-channel modes for programming versatility.
- Allows simple power linking for up to 62 units at 230V for efficient setups.

SPECIFICATIONS

Optical

Light Source: 1 LED (quad-color RGBW) 40W, (2.55 A), 50,000 hours life expectancy

Beam Angle: 4° to 18°

Field Angle: 5° to 24°

Zoom Range: 4° to 24°

Illuminance (4°): 4280 lux @ 5 m

Illuminance (18°): 238 lux @ 5 m

Selectable PWM: 600 Hz, 1200 Hz, 2000 Hz, 2400 Hz, 6000 Hz, 25,000 Hz

Dynamic Effects

Dimmer: Electronic

Shutter/Strobe: Electronic

Zoom: Motorized

Strobe Rate: 0 to 25 Hz

Standalone Color Mixing: Yes

Color Temperature Presets: Yes

Dim Modes: 5

Built-in Automated Programs: Yes

Customizable Programs: Yes

Recall Custom Programs: Yes

Construction / Physical

Dimensions: 13.03 x 7.32 x 5.31 in (331x186x135 mm)

Weight: 7.8 lb (3.6 kg)

Exterior Color: Black

Housing Material: Magnesium

Accessory Holder/Gel Frame Size: 4.75 in (121 mm)

Connections

Power Connection: Edison (Local) plug to Seetronic Powerkon IP65

Power Input: Seetronic Powerkon IP65

Power Output: Seetronic Powerkon IP65

Data Connectors: 5-pin IP65 XLR

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX

DMX Channels: 9, 12 or 17

Modes/Personalities: 4 personalities (HSIC, SSP, TOUR, TR16)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 39 units @ 120 V; 58 units @ 208 V; 62 units @ 230 V

Power and Current: 44 W, 0.342 A @ 120 V, 60 Hz

Power and Current: 48W, 0.234 A @ 208 V, 60 Hz

Power and Current: 49 W, 0.218 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET, FCC

IP Rating: IP65, outdoor/wet, with pressure equalizing M12 GORE® valve

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Neutrik TRUE1 power linking cables

5-pin IP Rated DMX Cables

Color Blending Filters: DF60X1D, DF20D

What's Included

Seetronic Powerkon IP65 power cord