



COLORDash Accent 3

A compact accent fixture powered by a 20W RGBA LED, delivering a powerful and evenly mixed punch of saturated color in a narrow, high-quality beam. Perfectly suited for providing discreet accent lighting in tight spaces and for flicker-free on-camera use in broadcast or video production environments.

- A single 20W quad-color RGBA LED delivers a rich and evenly mixed palette.
- Customize the tight 9° beam to a wider 14° wash with the included filter.
- Achieve exceptionally smooth fades with five selectable dimming curves.
- Integrate into any rig with DMX and RDM control plus multiple channel personalities.
- A double-bracketed yoke provides versatile mounting options for hanging or floor use.
- Offers standalone operation with built-in programs, addressed via an OLED display.

SPECIFICATIONS

Optical

Light Source: 1 LED (quad-color RGBA) 20 W, (950 mA), 50,000 hours life expectancy.

Installed Optics: 7°

Beam Angle w/ filter: 14°

Field Angle w/ filter: 27°

Beam Angle w/o filter: 9°

Field Angle w/o filter: 16°

Lumens: w/o filter: 377 lm

Lumens: w/ filter: 393 lm

Illuminance (total) w/ filter: 175 lux @ 5 m

Illuminance (total) w/o filter: 486 lux @ 5 m

Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

Dynamic Effects

Dimmer: Electronic

Shutter/Strobe: Electronic

Strobe Rate: 0 to 25 Hz

Standalone Color Mixing: Yes

Dim Modes: 5

Built-in Automated Programs: Yes

Construction / Physical

Dimensions: 163 x 133 x 80 mm

Weight: 2.0 lb (0.9 kg)

Exterior Color: Black

Connections

Power Connection: Edison plug to hard-wired

Power Input: Hard-wired

Data Connectors: 5-pin XLR DMX input and output cable whips

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX, RDM

DMX Channels: 4, 7 or 11

Modes/Personalities: 3 personalities (4, 7, 11)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power and Current: 18 W, 0.141 A @ 120 V, 60 Hz

Power and Current: 21 W, 0.098 A @ 208 V, 60 Hz

Power and Current: 20 W, 0.087 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET

IP Rating: IP20, dry location

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

5-pin DMX Cables

What's Included

COLORDash Accent 3