

COLORDash Batten-Quad 6

A linear wash fixture featuring six individually controllable quad-color RGBA LEDs that produces a wide array of whites and richly saturated colors, while also enabling dynamic pixel-mapping effects.

Perfectly suited for uplighting, wall-grazing, and creating pixel-mapped displays in theatrical, concert, and broadcast applications.

- Produces a wide color temperature range from a warm 2,800 K to a cool 10,000 K.
- Delivers a 17° beam and a 33° field angle for smooth, even wash coverage.
- Maintains an even pixel pitch when linking units for creating seamless visual arrays.
- Operates silently and flicker-free, making it ideal for on-camera applications.
- Offers versatile DMX control with five personalities ranging from 4 to 28 channels.
- Features Neutrik® powerCON® in/out for linking up to 33 units at 230 V.



SPECIFICATIONS

Optical

Light Source: 6 LEDs (quad-color RGBA) 7 W, (500 mA), 50,000 hours life expectancy

Color Temperature (range): 2,800 to 10,000 K

Installed Optics: 20°

Beam Angle: 17°

Field Angle: 33°

Illuminance (total): 390.7 lux @ 5 m

PWM Frequency: 600 Hz

Dynamic Effects

Dimmer: Electronic

Shutter/Strobe: Electronic

Strobe Rate: 0 to 20 Hz

Standalone Color Mixing: Yes

Color Temperature Presets: Yes

Built-in Automated Programs: Yes

Construction / Physical

Dimensions: 22 x 2.6 x 6.5 in (560 x 65 x 164 mm)

Weight: 5 lb (2.3 kg)

Exterior Color: Black

Connections

Power Connection: Edison plug to Neutrik powerCON

Power Input: Neutrik powerCON

Power Output: Neutrik powerCON

Data Connectors: 3- and 5-pin XLR

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX

DMX Channels: 4, 6, 10, 24 or 28

Modes/Personalities: 5 personalities (4, 6, 10, 24, 28)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 17 units @ 120 V; 30 units @ 208 V; 33 units @ 230 V

Power and Current: 90 W, 0.76 A @ 120 V, 60 Hz

Power and Current: 94 W, 0.45 A @ 208 V, 50 Hz

Power and Current: 96 W, 0.41 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET

IP Rating: IP20, dry location

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Neutrik powerCON cables

3- or 5-pin DMX Cables

What's Included

COLORDash Batten-Quad 6

Neutrik powerCON power cord

2 Trunnions