



## COLORDash Par-Quad 7

An ultra-compact and durable wash light equipped with seven quad-colored RGBW LEDs to project a vast range of saturated colors and variable white tones without creating multi-colored shadows. Its compact size and split-yoke bracket make it perfect for low-profile uplighting and installation in tight spaces for theatrical, architectural, or small event applications.

- Offers precise color mixing and an adjustable CCT range of 2800K to 10000K.
- Provides a fixed 18° beam angle and 32.5° field angle for consistent wash coverage.
- Features selectable 4, 6, or 10-channel DMX personalities for flexible control.
- Simplifies setup with power linking for up to 39 units via locking powerCON connectors.
- Ensures silent, flicker-free operation ideal for broadcast and studio applications.
- Built with a robust all-metal housing for long-term durability and professional use.

### SPECIFICATIONS

#### Optical

**Light Source:** 7 LEDs (quad-color RGBW) 7 W, (500 mA), 50,000 hours life expectancy

**Color Temperature (range):** 2800 to 10000 K

**Installed Optics:** 20°

**Beam Angle:** 18°

**Field Angle:** 32.5°

**Illuminance:** 434 lux @ 5 m

**PWM Frequency:** 600 Hz

#### Dynamic Effects

**Dimmer:** Electronic

**Shutter/Strobe:** Electronic

**Strobe Rate:** 0 to 20 Hz

**Standalone Color Mixing:** Yes

**Color Temperature Presets:** Yes

**Dim Modes:** 4

**Built-in Automated Programs:** Yes

#### Construction / Physical

**Dimensions:** 9.59 x 4 x 9.93 in (243 x 101 x 252 mm)

**Weight:** 5.4 lb (2.5 kg)

**Exterior Color:** Black

**Accessory Holder/Gel Frame Size:** 7.5 in/191 mm accessories

#### Connections

**Power Connection:** Local plug to Neutrik powerCON

**Power Input:** Neutrik powerCON

**Power Output:** Neutrik powerCON

**Data Connectors:** 3- and 5-pin XLR

**Cable Length (power):** 5 ft (1.5 m)

#### Control

**Control Protocol:** DMX

**DMX Channels:** 4, 6 or 10

**Modes/Personalities:** 3 personalities (4, 6, 10)

#### Electrical

**Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)

**Power Linking:** 21 units @ 120 V; 36 units @ 208 V; 39 units @ 230 V

**Power and Current:** 73 W, 0.60 A @ 120 V, 60 Hz

**Power and Current:** 73 W, 0.36 A @ 208 V, 50 Hz

**Power and Current:** 74 W, 0.35 A @ 230 V, 50 Hz

#### Certifications / Qualifications

**Certifications:** CE, MET

**IP Rating:** IP20, dry location

#### Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Neutrik powerCON Cables

3-pin or 5-pin DMX Cables

Color Blending Filters: DF60X1D, DF20D

## What's Included

COLORDash Par-Quad 7  
Neutrik powerCON power cord  
Gel frame holder (7.5 in/191 mm accessories)  
Gel frame