

DRB-F100CMIP

The DRB-F100CMIP and DRB-F50CMIP are IP65-rated rig bars that perform the dual function of hanging a video wall overhead or adapting it for ground stacking. Ideal for professional productions needing a flexible, all-weather solution for deploying video walls in either flown or ground-supported setups.

- Provides flexible mounting options for hanging panels either vertically or horizontally.
- Designed for seamless integration with F2, F3X, F5IP, and F4XIP video panels.
- Features a rugged, IP65-rated construction for reliable all-weather use.
- Equipped with a hoist ring that accommodates standard 1/2-inch and 5/8-inch shackles.
- Includes a clamp attachment bracket for direct connection to truss with M12 bolts.
- Adapts for ground stacking applications with the addition of the GROUND SUPPORT 2KIT.



SPECIFICATIONS

Construction / Physical

Dimensions: 39.35 x 2.36 x 4.72 in (999.6 x 60 x 120 mm)

Weight: 15.4 lb (7.0 kg)

Exterior Color: Black

Housing Material: Aluminum extrusion, stainless steel

Clamp

Load Capacity: (hanging): 1,665 lb (755 kg)

Load Capacity: (stacking): 2,735 lb (1,240kg)

Recommended Shackle Sizes: 1/2", 5/8"

Certifications / Qualifications

Certifications: ROHS

IP Rating: IP65, temporary outdoor/wet use

Required Accessories

Compatible Mounting Options: Shackle (Sizes: 1/2", 5/8"), Pipe Clamp (M12 threaded bolt)

Optional Accessories

DRB-CURVEKITX2

What's Included

1pcs F-series Dual Function Rig Bar-100 cm (DRB-F100CMIP)

1pcs 0° Linking Plate

2pcs clamp attachment brackets (DRB-CTC)

2pcs clamp bolts for TRUSST CTC-50HC