

# DRB-F50CMIP

A dual-function, IP65-rated rigging bar designed for both overhead hanging and ground stacking of video wall panels.

Perfect for building flown or ground-supported video walls in temporary event production or permanent installation applications where weather resistance is required.

- Features a rugged, IP65-rated design for reliable outdoor and touring applications.
- Enables both vertical and horizontal orientation of panels for maximum design flexibility.
- Designed for seamless integration with F2, F3X, F5IP, and F4XIP video panels.
- Features an integrated hoist ring for standard 1/2-inch and 5/8-inch shackles.
- Includes a DRB-CTC bracket for direct M12 bolt connection to truss.
- Converts for ground stacking applications with the optional GROUND SUPPORT 2KIT.



## SPECIFICATIONS

### Construction / Physical

**Dimensions:** 19.6 x 2.3 x 4.3 in (499 x 60 x 120 mm)

**Weight:** 8.8 lb (3.99 kg)

**Exterior Color:** Black

**Housing Material:** Aluminum extrusion, stainless steel

### Clamp

**Load Capacity (Hanging):** 970 lb (440 kg)

**Load Capacity (Stacking):** 2,204.6 lb (1,000 kg)

**Recommended Shackle Sizes:** 1/2", 5/8"

### Certifications / Qualifications

**Certifications:** ROHS

**IP Rating:** IP65, temporary outdoor/wet use

### Required Accessories

Compatible Mounting Options: Shackle (Sizes: 1/2", 5/8"), Pipe Clamp (M12 threaded bolt)

### Optional Accessories

DRB-CURVEKITX2

### What's Included

1pcs F-series Dual Function Rig Bar-50 cm (DRB-F50CMIP)

1pcs 0° Linking Plate

1pc clamp attachment brackets (DRB-CTC)

1pc clamp bolts for TRUSST CTC-50HC