



Epix Line 10 IP 10-Pack Road Case

A rolling road case that includes 10 EPIX Line 10 IP fixtures with all accessories, clamps, and multiple filter options. The case can be configured to hold up to 20 fixtures.

- Rolling case packed with 10pcs Epix Line 10 IP fixtures packed with all accessories included single pack fixtures; 2x clamps installed on each fixture
- Ability to remove additional light filters to pack 10-more Epix Line 10 IP fixtures (20-total per case)

SPECIFICATIONS

Optical

Light Source: 100 SMD 2727LEDs (tri-color RGB), 50,000 hours life expectancy

Beam Angle (open optics): 115.2°

Field Angle (open optics): 163°

Viewing Angle (open optics): 171.6°

Lumens:

open optics: 1,538

square milky white optics: 784

square black stealth optics: 239

round milky white optics: 943

Pixel Pitch: 10 mm

Display Refresh Rate: 4,900 Hz

Dynamic Effects

Strobe Rate: 0 to 30 Hz

Construction / Physical

Dimensions:

no filter: 39.37 x 1.161 x 2.862 in (1,000 x 29.5 x 72.7 mm)

square filter installed: 39.37 x 1.228 x 2.953 in (1,000 x 31.20 x 75 mm)

round filter installed: 39.37 x 1.969 x 4.63 in (1,000 x 50 x 117.6 mm)

road case: 47.2 x 23.6 x 29.6 in (1200 x 600 x 752 mm)

Weight: 176 lb (79.8 kg)

Exterior Color: Black

Housing Material: Aluminum alloy, Aluminum die-cast, High-impact flame-retardant polymer, Steel

Connections

Power Supply (remote driver): Epix D4 IP

Physical Linking (Standard Mode): 10 inline EPIX Line 10 IP

Physical Linking (Hi Power Mode): 6 inline EPIX Line 10 IP

Data Connectors: 4-pin IP65 XLR

Minimum required device linking cable size: 4 conductor (2 x 14 AWG, 2 x 16 AWG)

Cable Shielding: compatible with both shielded and unshielded cables

Control

DMX Channels: 2, 18, Groups of 5/10/25/50, or 300

Electrical

Input Voltage: 48 VDC

Power and Current (Standard): 21 W, .44 A @ 48 VDC

Power and Current (Hi Power): 32 W, .671 A @ 48 VDC

Required Accessories

KLSTR Software

Epix D4 IP Controller

Optional Accessories

EPIXMNTSPIGOT (Epix Mounting Bracket: Spigot Adapter 28mm)

EPIXMNTANGLE (Epix Mounting Bracket: +/- 120° Angling Adapter)

M12/1/2" BOLT

Clamps

RIGLINK 4-PIN XLR Cables

What's Included

- 10 EPIX LINE 10 IP
- 10 INTERLOCKING BRACKET
- 10 BLACK STEALTH SQUARE FILTER (INCLUDED)
- 10 MILKY WHITE ROUND FILTER (INCLUDED)
- 20 CTC-SLC CLAMPS (INSTALLED)