



Ovation ETD-40WW

A compact, track-mountable 40W warm white LED ellipsoidal with high CRI, zooming optics, and framing shutters for creating a precise, hard-edged beam for gobo projection.

Ideal for architectural and retail installations requiring a versatile, high-quality fixture to precisely highlight specific areas or products.

- Delivers 40W of warm white light with an exceptional 93 CRI for accurate color rendering.
- Offers a manual zoom range from a tight 19° spot to a wider 36° wash.
- Allows for precise beam shaping with integrated, manually-operated framing shutters.
- Accepts standard size E glass or metal gobos for versatile pattern projection.
- Designed for fast installation on most common track lighting systems.
- Operates efficiently with a low power consumption of only 37W at 120V.

SPECIFICATIONS

Optical

Light Source: 1 LEDs (WW) 40 W, (600 mA), 50,000 hours life expectancy.

Color Temperature (at full): 3255 K

CRI: 93

TLCI: 92.2

Beam Angle (w/19-36° lens)(19°): 16°

Beam Angle (w/19-36° lens)(26°): 17°

Beam Angle (w/19-36° lens)(36°): 18°

Field Angle (w/19-36° lens)(19°): 19°

Field Angle (w/19-36° lens)(26°): 25°

Field Angle (w/19-36° lens)(36°): 33°

Lumens (w/19-36° lens)(19°): 1,327

Lumens (w/19-36° lens)(26°): 1,260

Lumens (w/19-36° lens)(36°): 1,050

Illuminance (w/19-36° lens)(19°): 784 lux @ 5 m

Illuminance (w/19-36° lens)(26°): 526 lux @ 5 m

Illuminance (w/19-36° lens)(36°): 352 lux @ 5 m

Dynamic Effects

Dimmer: Electronic

Focus: Manual

Construction / Physical

Dimensions: 14.82 x 5.09 x 5.18 in (376.5 x 129.3 x 131.64 mm)

Weight: 3.4 lb (1.6 kg)

Exterior Color: Black

Housing Material: Aluminum die-cast

Gobo Size (Optional): Gobo size: 37.5 mm (outside), 20 mm (image, glass), 25 mm (image, steel), 1 mm (max. thickness)

Connections

Power Connection: Track Type H

Cable Length (power): 1.17 ft (0.36 m)

Electrical

Input Voltage: 120 VAC, 60 Hz

Input Voltage: 230 VAC, 50 Hz

Power and Current: 37 W, 0.291 A @ 120 V, 60 Hz

Power and Current: 39 W, 0.17 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET

IP Rating: IP20, dry location

Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

What's Included

Ovation ETD-40WW

Track Adaptor

Gobo holder size: 37.5 mm (outside), 20 mm (image, glass), 25 mm (image, steel), 1 mm (max. thickness)

Gel frame (2.75 in/70 mm accessories)