



Ovation GR-1 Adapter

The Ovation GR-1 Adapter is a durable power and data interface that enables the use of the outdoor-rated Ovation GR-1 IP gobo rotator with any ERS-style fixture. Ideal for theatrical, event, and production environments looking to integrate advanced gobo rotation capabilities into their existing ERS-style lighting inventory.

- Provides a universal power and data interface for the Ovation GR-1 IP rotator.
- Mounts securely to the yoke of an ERS-style fixture for simple, stable installation.
- Delivers dedicated powerCON output to operate the Ovation GR-1 IP gobo rotator.
- Features 5-pin DMX and RDM connections for seamless lighting console integration.
- Includes an onboard display for quick DMX addressing and manual configuration.
- Offers auto-ranging 100-240 VAC power input for versatile global operation.

SPECIFICATIONS

Construction / Physical

Dimensions: 3.7 x 2.1 x 5.3 in (95 x 53.1 x 135.7 mm)
Weight: 0.6 lb (0.3 kg)
Exterior Color: Black
Housing Material: High-impact, flame retardant polymer, Steel

Connections

Power Connection: Neutrik powerCON linking
Data Connectors: 5-pin XLR
Cable Length (power): 2ft 6 in (0.792 m)

Control

Control Protocol: DMX, RDM
DMX Channels: 1
Modes/Personalities: 1 personalities (1Ch)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
Power and Current: 6 W, .092 A @ 120 V, 60 Hz
Power and Current: 5 W, .063 A @ 208 V, 60 Hz
Power and Current: 5 W, .060 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE
IP Rating: IP20, dry location
Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

What's Included

Ovation GR-1 Adapter
 Neutrik powerCON power linking cord