



Ovation GR-1 IP

An IP65-rated gobo rotator accessory that provides dynamic pattern projection for Ovation E-260WW IP and E-910FC IP fixtures by drawing power and control directly from the host unit.

Perfect for adding textured lighting and logos to outdoor theatrical productions, themed environments, and architectural designs where weather resistance is crucial.

- Spins a single gobo or two gobos in counter-rotating directions for layered pattern effects.
- Connects via a dedicated port for integrated power and control from the host fixture.
- Delivers a wide variable speed range from 0.047 to 21 RPM for precise effect control.
- Provides fully indexable gobo positioning via DMX for precise and repeatable pattern alignment.
- Accepts standard B-size metal, glass, or effect gobos for maximum creative flexibility.
- Features a smooth stepper motor drive for exceptionally quiet and fluid gobo rotation.

SPECIFICATIONS

Dynamic Effects

Gobos size: B (metal, glass or effect)

Effects: CW or CCW Rotation, indexing, infinite rotation at variable speeds

Speed Range: 0.047 – 21 RPM (17° – 7,560° per minute)

Construction / Physical

Dimensions: 10.9 x 4.7 x 2.2 in (277.5 x 120.5x 56.9 mm)

Weight: 2.4 lb (1.2 kg)

Exterior Color: Black

Housing Material: Aluminum die-cast

Connections

Power Connection: Proprietary 4-pin IP65 input power/data cord (19 in/483 mm)

Data Connectors: Proprietary 4-pin IP65 input power/data cord (19 in/483 mm)

Cable Length (power/data): 19 in/483 mm

Control

Control Protocol: DMX

DMX Channels: 1

Electrical

Input Voltage: 24 VDC, 372 mA (via Ovation E-260WW IP)

Certifications / Qualifications

Certifications: CE

IP Rating: IP65, temporary outdoor/wet use

Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

What's Included

Ovation GR-1 IP
Power & Data Control Cable