

Ovation Rêve 3 Profile

This profile moving head features a full-spectrum RGBACM LED engine, delivering unparalleled color rendering and precision for professional lighting applications.

Engineered for the demands of theater, broadcast, and worship, it empowers designers with a powerful tool for creating immersive and dynamic visual experiences.

- Fully featured moving head profile fixture with red, green, blue, cyan, amber and mint full spectrum LEDs with CRI >98. Fixture also features a four-blade framing shutter system with +/- 60° rotation, animation wheel, an 8:1 zoom, prism, variable frost, as well as static and rotating gobo wheels.
- Part of a complete ecosystem within the Ovation family, sharing the same color attributes so that colors match across the series.
- Multiple fan modes including OFF allowing this fixture to be used in a multitude of applications.
- 22-bit dimming with user selectable red shift of master dimmer for smooth control of fades.
- +/- green adjustment for on-camera hue correction.
- PWM, dimmer speed, dimmer curves, and fan settings from the control channel and over RDM.
- Attachable accessory holder for gel frames, top hats, and the like.
- Camera holder kit sold as an accessory.
- Dedicated camera connection port (Ethercon).
- NFC configuration with app.
- Battery backup display with auto-rotate depending on fixture orientation.
- Ethernet pass through.
- True 1 compatible power input/output.

SPECIFICATIONS

Optical *

Light Source: 85 LEDs ((14 red, 10 green, 11 blue, 4 cyan, 20 amber, 26 mint), 50,000 hours life expectancy

** These specifications are still being finalized. Speak to a salesperson for more information.*

Dynamic Effects

Pan and Tilt: 540°/270°

Colors: Red, Green, Blue, Cyan, Amber, Mint

Gobos (1): 7 + open (7 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds

Gobos (2): 8 + open (8 glass), indexing, slot-n-lock, continuous scroll at variable speeds

Effect Wheel: 1

Framing Shutters: 4

Iris: yes

Prism: (1) six facet

Construction / Physical

Dimensions: 16.10 x 11.02 x 27.24 in (410 x 280 x 692 mm)

Weight: 68 lb (30.9 kg)

IP Rating: 20

Connections

Power Connection: Edison plug to Seetronic Powerkon IP65

Power Input: Seetronic Powerkon IP65

Power Output: Seetronic Powerkon IP65

Data Connectors: 5-pin XLR, Amphenol XLR Net RJ45 connectors in/out

Control

Control Protocol: Art-Net, sACN, DMX, CRMX (optional)

Electrical

Input Voltage:

Power and Current: 1150 W, 9.56 A @ 120 V, 60 Hz

Power and Current: 1116 W, 5.45 A @ 208 V, 60 Hz

Power and Current: 1111 W, 4.91 A @ 230 V, 50 Hz

Certifications / Qualifications

Compliance: CE, MET, FCC, CB