



## Ovation SP-300CW

A quiet, medium-throw LED followspot that projects a crisp cool white beam and provides comprehensive manual control over dimming, iris, zoom, focus, and color changing.

Perfect for theatrical productions, houses of worship, and other performance venues where a quiet, manually-operated fixture is essential for medium-throw applications.

- Powered by a 260 W LED source delivering a 5640 K color temperature with a high CRI.
- Provides a versatile 9° to 17° manual zoom range for flexible beam sizing.
- Features a 24-leaf iris for precise beam shaping and a complete blackout.
- Includes a six-position, removable boomerang for quiet, manual gel color changes.
- Engineered for virtually silent operation, making it ideal for studios and theaters.
- Ships as a complete system that includes the followspot and a dedicated stand.

### SPECIFICATIONS

#### Optical

**Light Source:** 1 LEDs (CW) 260 W, (3.6 A), 5,640 K, 50,000 hours life expectancy

**Color Temperature (at full):** 5640 K

**CRI:** 88

**Beam Angle:** 9° to 13°

**Field Angle:** 9° to 17°

**Zoom Range:** 9° to 17°

**Illuminance (Narrow):** 15,400 lux @ 5 m

**Illuminance (Wide):** 7,070 lux @ 5 m

**PWM Frequency:** 2300 Hz

#### Dynamic Effects

**Colors:** 6 + white

**Dimmer:** Manual, Linear

**Zoom:** Manual

**Focus:** Manual

**Iris:** 24-leaf, full blackout

#### Construction / Physical

**Dimensions:** 44.7 x 13.9 x 15.8 in (1,137 x 354 x 403 mm)

**Dimensions (Stand with fixture, optimal open):** 46.8 x 13.98 x 62.4 in (1,189 x 355 x 1,585 mm)

**Diameter (Stand with fixture, optimal open):** 33.8 in (stand) 52.8 in (fixture)

**Dimensions (Stand with fixture, max open):** 46.8 x 13.98 x 81.6 in (1,189 x 355 x 2,073 mm)

**Diameter (Stand with fixture, max open):** 39.6 in (stand) 52.8 in (fixture)

**Weight:** 52.8 lb (24 kg)

**Exterior Color:** Black

**Housing Material:** Steel

#### Connections

**Power Connection:** Edison (Local) plug to Seetronic Powerkon (powerCON Compatible)

**Power Input:** Seetronic Powerkon (powerCON Compatible)

**Cable Length (power):** 5 ft (1.5 m)

#### Electrical

**Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)

**Power and Current:** 223 W, 2.22 A @ 100 V, 60 Hz

**Power and Current:** 207 W, 1.73 A @ 120 V, 60 Hz

**Power and Current:** 197 W, 1.03 A @ 208 V, 60 Hz

**Power and Current:** 197 W, 0.94 A @ 230 V, 50 Hz

**Power and Current:** 194 W, 0.90 A @ 240 V, 50 Hz

#### Certifications / Qualifications

**Certifications:** CE, MET, FCC

**IP Rating:** IP20, dry location

**Temperature (Ambient):** -4 °F to 113 °F (-20 °C to 45 °C)

#### What's Included

Ovation SP-300CW

Seetronic Powerkon IP65 power cord

Tripod stand

Starter pack of gels