

RIGLINK IP65 DMX Cables



An IP65-rated, production-grade DMX lighting cable engineered to provide reliable signal transmission and robust connections.

Perfect for professional touring, live events, and permanent installations where dependable, weatherproof connectivity is essential.

- Features a double-shielded design with a high-torsion OFC core for superior signal protection.
- Engineered for 110Ω DMX-512 applications with low-capacitance insulation for signal stability.
- Equipped with professional-grade Seetronic® connectors to ensure a robust and reliable connection system.
- Built with a highly elastic and durable PVC outer jacket for flexibility in touring applications.
- Offers color-coded connectors for quick and easy identification of cable lengths during setup.
- Available in multiple standard lengths to accommodate a wide variety of professional setups.

SPECIFICATIONS

Construction / Physical	Electrical
Conductor Specification: 2 x 0.22mm ² (24AWG)	Withstand Voltage: 0.5kV
Conductor Structure: OFC 20/0.12BC	Conductor Resistance: 88.2 Ω/km
Insulation Material: LDPE	Capacitance between Conductors: 50 pF/m
Insulation OD: 1.8mm	Conductor and Shield Capacitance: 122 pF/m
Shield Structure: OFC 16/8/0.1TC + AL	Impedance: 110 Ω
Outer Jacket Material: PVC (Black)	
Outer Diameter: 6.0 ± 0.2mm	
Temperature Rating: -20°C – 70°C	
	Cable
	Metric: 1m, 3m, 5m, 10m, 20m
	Imperial: 1.5ft, 5ft, 10ft, 25ft, 50ft

VARIATIONS

Length	SKU	Description
1.5FT	RIGLINKIPDMX18IN	RIGLINK IP65 DMX Cables – 1.5FT
1M	RIGLINKIPDMX1M	RIGLINK IP65 DMX Cables – 1M
5FT	RIGLINKIPDMX5FT	RIGLINK IP65 DMX Cables – 5FT
3M	RIGLINKIPDMX3M	RIGLINK IP65 DMX Cables – 3M
10FT	RIGLINKIPDMX10FT	RIGLINK IP65 DMX Cables – 10FT
5M	RIGLINKIPDMX5M	RIGLINK IP65 DMX Cables – 5M
25FT	RIGLINKIPDMX25FT	RIGLINK IP65 DMX Cables – 25FT
10M	RIGLINKIPDMX10M	RIGLINK IP65 DMX Cables – 10M
50FT	RIGLINKIPDMX50FT	RIGLINK IP65 DMX Cables – 50FT
20M	RIGLINKIPDMX20M	RIGLINK IP65 DMX Cables – 20M