



RIGLINK TR1 Cables

An IP65-rated and UL-certified copper-stranded power cable featuring production-grade Seetronic® connectors for dependable power delivery in professional settings. Perfect for powering lighting, audio, and video equipment in demanding indoor or outdoor environments, including tours, festivals, and live event productions.

- Constructed with stranded, oxygen-free copper for reliable power transmission.
- Engineered for road-ready durability in both touring and permanent installations.
- Features color-coded connectors for quick identification of cable lengths.
- Certified components meet global safety standards for international productions.
- Delivers efficient power flow with a low conductor resistance of 7.8 Ω/km.
- Offered in various lengths marked in both meters and feet for convenience.

SPECIFICATIONS

Construction / Physical	Electrical
<p>Conductor Specification: 3 x 2.08mm² (14AWG)</p> <p>Conductor Structure: OFC 41/0.25BC</p> <p>Insulation Material: PVC</p> <p>Insulation OD: 3.45mm</p> <p>Outer Jacket Material: PVC (Black)</p> <p>Outer Diameter: 9.2 ± 0.2mm</p> <p>Temperature Rating: -20°C – 105°C</p>	<p>Voltage Rating: 300 V/500 V</p> <p>Conductor Resistance: 7.8 Ω/km</p>
	Cable
	<p>Imperial: 1.5ft, 5ft, 10ft, 25ft, 50ft</p>

VARIATIONS

Length	SKU	Description
1.5FT	RIGLINKTR118IN	RIGLINK TR1 Cables – 1.5FT
1M	RIGLINKTR11M	RIGLINK TR1 Cables – 1M
5FT	RIGLINKTR15FT	RIGLINK TR1 Cables – 5FT
3M	RIGLINKTR13M	RIGLINK TR1 Cables – 3M
10FT	RIGLINKTR110FT	RIGLINK TR1 Cables – 10FT
5M	RIGLINKTR15M	RIGLINK TR1 Cables – 5M
25FT	RIGLINKTR125FT	RIGLINK TR1 Cables – 25FT
10M	RIGLINKTR110M	RIGLINK TR1 Cables – 10M
50FT	RIGLINKTR150FT	RIGLINK TR1 Cables – 50FT
20M	RIGLINKTR120M	RIGLINK TR1 Cables – 20M