



RIGLINK 4-Pin Cables

A rugged, IP65-rated Riglink cable that integrates both power and DMX data transmission into a single line, featuring robust Seetronic® connectors for secure and dependable lighting control.

Perfectly suited for touring productions, outdoor events, and any lighting setup requiring a streamlined and weather-resistant cabling solution.

- Features a highly elastic PVC outer jacket for a durable and flexible cable body.
- Ideal for both permanent installations and demanding mobile touring applications.
- Designed for seamless compatibility with ÉPIX, STRIKE Array 1, and other 4-pin products.
- Offers color-coded connectors to quickly identify different cable lengths on site.
- Certified components meet global safety standards for reliable and compliant operation.
- Built rugged for live production with a high withstand voltage rating of 1.5kV.

SPECIFICATIONS

Construction / Physical	Electrical
<p>Conductor Specification: 2 x 0.75mm² (18AWG) & 2 x 2.5mm² (13AWG)</p> <p>Conductor Structure: OFC 24/0. 2BC & OFC 50/0.25BC</p> <p>Insulation Material: PVC</p> <p>Insulation OD: 2.4mm & 3.5mm</p> <p>Outer Jacket Material: PVC (Black)</p> <p>Outer Diameter: 9.5 ± 0.2mm</p> <p>Temperature Rating: -20°C – 70°C</p>	<p>Withstand Voltage: 1.5kV</p> <p>Conductor Resistance: 25.98 Ω/km & 7.98 Ω/km</p>
	Cable
	<p>Metric: 1m, 3m, 5m, 10m, 20m</p> <p>Imperial: 1.5ft, 5ft, 10ft, 25ft, 50ft</p>

VARIATIONS

Length	SKU	Description
1.5FT	RIGLINKXLR418IN	RIGLINK 4-Pin Cables – 1.5FT
1M	RIGLINKXLR41M	RIGLINK 4-Pin Cables – 1M
5FT	RIGLINKXLR45FT	RIGLINK 4-Pin Cables – 5FT
3M	RIGLINKXLR43M	RIGLINK 4-Pin Cables – 3M
10FT	RIGLINKXLR410FT	RIGLINK 4-Pin Cables – 10FT
5M	RIGLINKXLR45M	RIGLINK 4-Pin Cables – 5M
25FT	RIGLINKXLR425FT	RIGLINK 4-Pin Cables – 25FT
10M	RIGLINKXLR410M	RIGLINK 4-Pin Cables – 10M
50FT	RIGLINKXLR450FT	RIGLINK 4-Pin Cables – 50FT
20M	RIGLINKXLR420M	RIGLINK 4-Pin Cables – 20M