



Rogue Outcast 1 Beam

An IP65-rated moving head beam fixture that creates intensely bright aerial effects using a 14-position color wheel, overlapping prisms, frost, and 17 static gobos. Perfect for outdoor tours, festivals, and large-scale events that require powerful, weather-resistant, and creative aerial beam effects.

- Features a powerful USHIO 300W lamp delivering 154,000 lux at 15 meters.
- Projects a razor-sharp 1.2-degree beam for precise, high-impact aerial effects.
- Creates complex mid-air looks with layerable 8-facet and 5-facet prisms.
- Built with a rugged IP65-rated housing for reliable temporary outdoor use.
- Delivers fast, precise 540° pan and 270° tilt for dynamic fixture positioning.
- Offers versatile system integration with both DMX and RDM protocol support.

SPECIFICATIONS

Optical

Light Source: USHIO NSL-300W lamp, 8000 K, 8,000 hours life expectancy

Color Temperature (at full): 7115 K

CRI: 73.9

Beam Angle: 1.2°

Field Angle: 2.1°

Illuminance (total): 154,000 lux @ 15 m

Dynamic Effects

Pan and Tilt: 540°/270°

Pan and Tilt Ranges: 540°, 360°, 180° pan/270°, 180°, 90° tilt

Colors: 14 + white, split colors, continuous scroll at variable speeds

Gobos: 17 + open (17 metal), continuous scroll at variable speeds

Dimmer: Motorized

Shutter/Strobe: Motorized

Focus: Motorized

Frost: Motorized

Prism: 5 Facets, motorized, rotating

Prism: 8 Facets, motorized, rotating

Move-in-Black: Yes

Construction / Physical

Dimensions: 16.23 x 12.2 x 23.19 in (412.2 x 310 x 589.1 mm)

Weight: 70.2 lb (32 kg)

Exterior Color: Black

Housing Material: Aluminum die-cast

Connections

Power Connection: Edison plug to Seetronic Powerkon IP65 Power Input: Seetronic Powerkon IP65

Power Input: Seetronic Powerkon IP65

Data Connectors: 5-pin IP rated

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX, RDM

DMX Channels: 16 or 19

Modes/Personalities: 2 personalities (16, 19)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power and Current: 451 W, 3.81 A @ 120 V, 60 Hz

Power and Current: 436 W, 2.09 A @ 208 V, 60 Hz

Power and Current: 408 W, 1.76 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET

IP Rating: IP65, temporary outdoor/wet use

Temperature (Ambient): 14 °F to 104 °F (-10 °C to 40 °C)

Optional Accessories

Professional Clamps : CTC-50HC, CTC-50HCN

Safety Cable: SC-07

DMX Cables

IP Rated Seetronic® Powerkon Extensions

What's Included

- Rogue Outcast 1 Beam
- Seetronic Powerkon IP65 power cord
- 2 Omega brackets with mounting hardware
- Quick Reference Guide