



# Rogue Outcast 1 BeamWash

A lightweight, IP65-rated LED fixture combining beam and wash effects with a wide zoom range and a pixel-mappable outer ring for creative visual impact. Ideal for touring productions, festivals, and any event requiring a compact, all-weather fixture that delivers a versatile range of beam, wash, and pixel effects.

- Features seven 45W RGBW LEDs, producing a punchy and vibrant 4,073-lumen output.
- Delivers a wide 3.9° to 55.3° zoom range for flexible beam or wash applications.
- Create dynamic visuals with a 12-zone, pixel-mappable RGB ring under a stealth filter.
- Provides advanced control with 16-bit dimming, six dimming modes, and selectable PWM settings.
- A compact, 20 lb IP65-rated body ensures all-weather reliability for touring and events.
- Offers versatile control via DMX and RDM, plus a USB-C port for easy software updates.

## SPECIFICATIONS

### Optical

**Field Angle:** 5.9° to 49.8°

**Cutoff Angle:** 6.7° to 55.3°

**Zoom Range:** 3.9° to 55.3°

**Lumens – Source:** 5,900

**Lumens – Output:** 4,073

**Illuminance (3.9°):** 15,308 lux @ 5 m

**Illuminance (55.3°):** 473 lux @ 5 m

**Selectable PWM:** 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 15,000 Hz

### Dynamic Effects

**Pan and Tilt:** 540°/260°

**Pan and Tilt Ranges:** 180°, 360°, 540° pan/90°, 180°, 260° tilt

**Dimmer:** Electronic

**Shutter/Strobe:** Electronic

**Zoom:** Motorized

**Strobe Rate:** 0 to 20 Hz

**Standalone Color Mixing:** Yes

**Color Temperature Presets:** Yes

**Dim Curves:** 4

**Built-in Automated Programs:** Yes

**Customizable Programs:** yes

**Recall Custom Programs:** No

### Construction / Physical

**Dimensions:** 11.92 x 7.58 x 15.75 in (303 x 192 x 391 mm)

**Weight:** 20.2 lb (9.16 kg)

**Exterior Color:** Black

**Housing Material:** Magnesium aluminum diecast, high impact, flame-retardant polymer

### Connections

**Power Connection:** Edison plug to Seetronic Powerkon IP65

**Power Input:** Seetronic Powerkon IP65

**Power Output:** Seetronic Powerkon IP65

**Data Connectors:** 5-pin XLR

**Cable Length (power):** 5 ft (1.5 m)

### Control

**Control Protocol:** DMX, RDM

**DMX Channels:** 15, 24, 30, 64, 111 or 135

**Modes/Personalities:** 6 personalities (15, 24, 30, 64, 111, 135)

### Electrical

**Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)

**Power Linking:** 3 units @ 120 V; 6 units @ 208 V; 7 units @ 230 V

**Power and Current:** 385 W, 3.25 A @ 120 V, 60 Hz

**Power and Current:** 376 W, 1.92 A @ 208 V, 60 Hz

**Power and Current:** 372 W, 1.69 A @ 230 V, 50 Hz

## Certifications / Qualifications

**Certifications:** CE, MET, FCC, UKCA

**IP Rating:** IP65, temporary outdoor/wet use, with pressure equalizing M12 GORE valve

**Temperature (Ambient):** -4 °F to 113 °F (-20 °C to 45 °C)

**Maximum Exterior Surface Temperature (Tc):** 80° C / 176° F

**Certifications:** Maximum Ambient Temperature (ta) 45° C / 113° F

## Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Safety Cable: SC-07

IP Rated Seetronic® Powerkon Extensions

DMX Cables

Flight Case:

UPLOAD 08 software uploader

## What's Included

Rogue Outcast 1 BeamWash

Seetronic Powerkon IP65 power cord

(2) Omega brackets with mounting hardware