



Rogue Outcast 1 Hybrid

An IP65-rated spot, beam, and wash hybrid moving head powered by an intense 400W lamp, featuring dual gobo wheels, two layerable prisms, and a 14-hue color wheel for a complete effects package.

Perfect for small to medium festivals and events needing a versatile, feature-packed, and outdoor-ready lighting fixture to create maximum visual impact.

- Offers an expansive linear zoom range from a tight 1° beam to a 29.1° spot.
- Features one wheel of 9 rotating glass gobos and one with 13 static metal gobos.
- Create complex aerals with layerable 6-facet linear and 8-facet round prisms.
- Achieve a smooth, consistent wash with integrated frost and beam flattening options.
- Supports both DMX and RDM protocols for flexible and advanced system control.
- A 6,000-hour lamp life and True 1 power input ensure operational reliability.

SPECIFICATIONS

Optical

Light Source: USHIO NSL-400 W lamp, 6632 K, 6,000 hours life expectancy

Color Temperature (at full): 6483 K

Lumens – Source: 14,575

Lumens – Output: 9,263

Spot Mode:

Beam Angle: 2.2° to 12.4°

Field Angle: 4.3° to 24.3°

Cutoff Angle: 5.2° to 29.1°

Zoom Range: 2.2° to 29.1°

Illuminance (24.3°): 5742 lux @ 5 m

Illuminance (4.3°): 209326 lux @ 5 m

Beam Mode:

Beam Angle: 1° to 5.2°

Field Angle: 1.8° to 12.6°

Cutoff Angle: 2.1° to 15.3°

Zoom Range: 1° to 15.3°

Illuminance (1.8°): 123,124 lux @ 15 m

Illuminance (12.6°): 3,517 lux @ 15 m

Wash Mode:

Beam Angle: 4.9° to 18°

Field Angle: 9.3° to 25.6°

Cutoff Angle: 12.4° to 28°

Zoom Range: 4.9° to 28.3°

Illuminance (25.6°): 1,570 lux @ 5 m

Illuminance (9.3°): 17,118 lux @ 5 m

Dynamic Effects

Pan and Tilt: 540°/260°

Pan and Tilt Ranges: 540°, 360°, 180° pan/260°, 180°, 90° tilt

Colors: 13 + white, split colors, continuous scroll at variable speeds

Gobos (1): 9 + open (9 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds

Gobos (2): 13 + open (13 metal), continuous scroll at variable speeds

Gobo Size: Gobo Wheel 1 (rotating glass): 15.9 mm (outside), 12 mm (image), 1.1 mm (max. thickness)

Dimmer: Motorized

Shutter/Strobe: Motorized

Zoom: Motorized

Focus: Motorized

Frost: Motorized

Prism: 6 Facets, motorized, rotating

Prism: 8 Facets, motorized, rotating

Move-in-Black: Yes

Construction / Physical

Dimensions: 15.91 x 12.20 x 30.16 in (404 x 310 x 766 mm)

Weight: 83.8 lb (38 kg)

Exterior Color: Black

Housing Material: Aluminum die-cast

Connections

Power Connection: Bare-wired to Seetronic Powerkon IP65

Power Input: Seetronic Powerkon IP65

Data Connectors: 5-pin IP rated

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX, RDM

DMX Channels: 20 or 25

Modes/Personalities: 2 personalities (20, 25)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power and Current: 514 W, 4.329 A @ 120 V, 60 Hz

Power and Current: 513 W, 2.501 A @ 208 V, 60 Hz

Power and Current: 520 W, 2.267 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET

IP Rating: IP65, temporary outdoor/wet use

Temperature (Ambient): 14 °F to 104 °F (-10 °C to 40 °C)

What's Included

Rogue Outcast Hybrid IP

Seetronic Powerkon IP65 power cord

2 Omega brackets with mounting hardware

Quick Reference Guide