

# Rogue Outcast 2 Beam



A lightweight, IP65-rated moving head beam fixture that harnesses a powerful 300W lamp to project an intensely bright, tight beam with multifaceted aerial looks from split colors, gobos, and rotating prisms.

Suited for both indoor and outdoor productions, including tours, festivals, and large-scale events that demand a powerful, weather-resistant fixture for creating cutting aerial beam effects.

- Features a 300W Ushio lamp projecting a razor-sharp 0.8° beam for intense, focused aerial effects.
- Built with a lightweight, IP65-rated alloy housing for reliable performance in any weather condition.
- Offers independently controlled and layerable 5-facet linear and 8-facet round prisms for dynamic visuals.
- Expands creative options with a 17-pattern static gobo wheel and a 14-color wheel for split-color effects.
- Includes a frost filter to create an even light distribution for versatile soft-edged wash looks.
- Supports both DMX and RDM protocols for comprehensive remote control and fixture management.

## SPECIFICATIONS

### Optical

**Light Source:** 300W NSL Ushio lamp, 8000 K (color temp), 8,000 hours life expectancy

**Color Temperature (at full):** 7353 K

**Front lens diameter:** 160 mm

**CRI:** 75.5

**Beam Angle:** 0.8°

**Field Angle:** 1.6°

**Cutoff Angle:** 2°

**Lumens – Output:** 29,130

**Illuminance (total):** 204,855 lux @ 15 m

### Dynamic Effects

**Pan and Tilt:** 540°/260°

**Pan and Tilt Ranges:** 540°, 360°, 180° pan/260°, 180°, 90° tilt

**Colors:** 14 + white, split colors, continuous scroll at variable speeds

**Gobos:** 17 + open (17 metal), 17 static, continuous scroll at variable speeds; size: 106 mm (outside), 6 mm (image), 0.6 – 0.8 mm (max. thickness)

**Dimmer:** Electronic

**Shutter/Strobe:** Motorized

**Focus:** Motorized

**Frost:** Motorized

**Prism:** 5 Facets, motorized, rotating

**Prism:** 8 Facets, motorized, rotating

**Move-in-Black:** Yes

### Construction / Physical

**Dimensions:** 14.41 x 9.61 x 22.6 in (366 x 244 x 574 mm)

**Weight:** 45.19 lb (20.5 kg)

**Exterior Color:** Black

**Housing Material:** Aluminum/Magnesium diecast

### Connections

**Power Connection:** Edison plug to Seetronic Powerkon IP65

**Power Input:** Seetronic Powerkon IP65

**Data Connectors:** 5-pin IP rated

**Cable Length (power):** 5 ft (1.5 m)

### Control

**Control Protocol:** DMX, RDM

**DMX Channels:** 16 or 18

**Modes/Personalities:** 2 personalities (16, 18)

### Electrical

**Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)

**Power and Current:** 413 W, 3.51 A @ 120 V, 60 Hz

**Power and Current:** 403 W, 2.01 A @ 208 V, 60 Hz

**Power and Current:** 404 W, 1.82 A @ 230 V, 50 Hz

## Certifications / Qualifications

**Certifications:** CE, MET, UKCA

**IP Rating:** IP65, temporary outdoor/ wet, with pressure equalizing M12 GORE valve

**Temperature (Ambient):** -14 °F to 113 °F (-10 °C to 45 °C)

**Maximum Exterior Surface Temperature (Tc):** 80° C / 176° F

**Maximum Ambient Temperature (Ta):** 45° C / 113° F

## Optional Accessories

Clamps

IP65 5 pin DMX Cables

IP65 PowerKon Extension cables

Flight Case

## What's Included

Rogue Outcast 2 Beam

Seetronic Powerkon IP65 power cord

(2) Omega brackets with mounting hardware