



Rogue Outcast 2 Hybrid

A rugged IP65-rated hybrid moving head that delivers powerful spot, beam, and wash effects using a bright 400W lamp, an expansive zoom range, dual gobo wheels, and layerable prisms.

Its durable, all-weather design makes it the ideal all-in-one workhorse for outdoor festivals, concert tours, and any production requiring versatile lighting in demanding conditions.

- Features a powerful 400W Ushio lamp with an 8000K color temperature and 6,000-hour life.
- Delivers a precise zoom from a tight 0.9° beam to a wide 14.5° spot.
- Creates complex aerial effects with layerable 5-facet linear and 8-facet round prisms.
- Offers two gobo wheels with 9 rotating glass and 13 static metal patterns.
- Housed in a lightweight, IP65-rated aluminum/magnesium body for all-weather reliability.
- Supports DMX and RDM protocols with flexible 20 and 25-channel control personalities.

SPECIFICATIONS

Optical

Light Source: Ushio NSL-400L W lamp, 8000 K, 6,000 hours life expectancy

Color Temperature (at full): 7009K

Front Lens size: 160mm

CRI: 86.1

Lumens - Output: 16,033

Spot Mode:

Beam Angle: 1.4° to 14.5°

Field Angle: 2.8° to 30°

Cutoff Angle: 3.5° to 37.2°

Zoom Range: 1.4° to 37.2°

Illuminance (1.4°): 790,297lux @ 5 m

Illuminance (37.2°): 6,787 lux @ 5 m

Beam Mode:

Beam Angle: 0.9° to 6.7°

Field Angle: 1.7° to 18.1°

Cutoff Angle: 2.1° to 20.7°

Zoom Range: 0.9° to 20.7°

Illuminance (0.9°): 180,594 lux @ 15 m

Illuminance (20.7°): 2,158 lux @ 15 m

Wash Mode:

Beam Angle: 5.4° to 32.1°

Field Angle: 9.5° to 39.4°

Cutoff Angle: 11.9° to 41.7°

Zoom Range: 5.4° to 41.7°

Illuminance (9.1°): 30,289 lux @ 5 m

Illuminance (41.7°): 1,309 lux @ 5 m

Dynamic Effects

Pan and Tilt: 540°/260°

Pan and Tilt Ranges: 540°, 360°, 180° pan/260°, 180°, 90° tilt

Colors: 13 + White, split colors, continuous scroll at variable speeds

Gobos (1): 9 + open (9 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds

Gobos (2): 13 + open (13 metal), continuous scroll at variable speeds

Gobo Size: Gobo Wheel 1 (rotating): 16 mm (outside), 12 mm (image), 1.1 mm (max. thickness)

Dimmer: Motorized

Shutter/Strobe: Motorized

Zoom: Motorized

Focus: Motorized

Frost: Motorized

Prism (1): 5 Facets, motorized, rotating

Prism (2): 8 Facets, motorized, rotating

Move-in-Black: Yes

Construction / Physical

Dimensions: 14.41 x 10.04 x 27.76 in (366 x 255 x 705 mm)

Weight: 54.4 lb (24.7 kg)

Exterior Color: Black

Housing Material: Aluminum alloy, Aluminum diecast, High-impact flame-retardant polymer

Connections

Power Connection: Bare-wired to Seetronic Powerkon IP65

Power Input: Seetronic Powerkon IP65

Data Connectors: 5-pin IP rated

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX, RDM

DMX Channels: 20 or 25

Modes/Personalities: 2 personalities (20, 25)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power and Current: 581 W, 4.95 A @ 120 V, 60 Hz

Power and Current: 565 W, 2.76 A @ 208 V, 60 Hz

Power and Current: 568 W, 2.53 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET, CB, UKCA

IP Rating: IP65, temporary outdoor/wet use

Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

Optional Accessories

Clamps

DMX Cables

Flight Cases

What's Included

Rogue Outcast 2 Hybrid

Seetronic Powerkon IP65 power cord

2 Omega brackets with mounting hardware