

## Rogue R1 Wash

A bright and versatile moving wash fixture powered by seven 15W RGBW quad-LEDs, offering a wide 11° to 48° zoom range and a unique bubble lens design for excellent color rendering and visual effects.

With its combination of performance and value, this fixture is a welcome addition to any touring rig or permanent installation.

- Delivers 3,500 source lumens from seven powerful 15W quad-color RGBW LEDs.
- Offers a motorized 11° to 48° zoom for flexible beam shaping and coverage.
- Features a unique bubble lens design for superior color blending without color shadows.
- Achieves exceptionally fast and smooth 540° pan and 230° tilt movements.
- Provides versatile control with 3- and 5-pin DMX and multiple channel profiles.
- Includes six distinct dimming modes for advanced control over fades and intensity.



### SPECIFICATIONS

#### Optical

**Light Source:** 7 LEDs (quad-color RGBW) 15 W, (980 mA), 50,000 hours life expectancy

**Color Temperature (range):** 2,800 to 10,000 K

**Beam Angle:** 8° to 30°

**Field Angle:** 11° to 48°

**Zoom Angle:** 11° to 48°

**Lumens – Source:** 3,500

**Lumens – Output:** 2,300

**Illuminance (11°):** 2,790 lux @ 5 m

**Illuminance (48°):** 261 lux @ 5 m

**PWM Frequency:** 1,200 Hz

#### Construction / Physical

**Dimensions:** 7.36 x 10.43 x 13.94 in (187 x 265 x 354 mm)

**Weight:** 13 lb (5.9 kg)

**Exterior Color:** Black

**Housing Material:** High-impact flame-retardant polymer

#### Connections

**Power Connection:** Edison (Local) plug to Neutrik powerCON

**Power Input:** Neutrik powerCON

**Power Output:** Neutrik powerCON

**Data Connectors:** 3- and 5-pin XLR

**Cable Length (power):** 5 ft (1.5 m)

#### Dynamic Effects

**Pan and Tilt:** 540°/230°

**Pan and Tilt Ranges:** 180°, 360°, 540° pan/90°, 180°, 230° tilt

**Dimmer:** Electronic

**Shutter/Strobe:** Electronic

**Zoom:** Motorized

**Strobe Rate:** 0 to 20 Hz

**Standalone Color Mixing:** Yes

**Color Temperature Presets:** Yes

**Dim Curves:** 4

**Built-in Automated Programs:** Yes

**Customizable Programs:** No

**Recall Custom Programs:** No

#### Control

**Control Protocol:** DMX

**DMX Channels:** 14, 15, 19 or 21

**Modes/Personalities:** 4 personalities (14CH, 15CH, 19CH, or 21CH)

#### Electrical

**Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)

**Power Linking:** 10 units @ 120 V; 18 units @ 208 V; 21 units @ 230 V

**Power and Current:** 161 W, 1.34 A @ 120 V, 60 Hz

**Power and Current:** 141 W, 0.72 A @ 208 V, 60 Hz

**Power and Current:** 139 W, 0.62 A @ 230 V, 50 Hz

#### Certifications / Qualifications

**Certifications:** CE, MET

**IP Rating:** IP20, dry location

## Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Safety Cable: SC-07

Neutrik powerCON cables

DMX Cables

Flight Case: CP6CASER1W

UPLOAD 08 software uploader

## What's Included

Rouge R1 Wash

Neutrik powerCON power cord

Omega bracket with mounting hardware