

STRIKE 4

The STRIKE 4 is a versatile audience blinder and strobe featuring four independently focusable, high-power COB LEDs that deliver energetic effects, smooth 16-bit dimming, and flexible control options.

With its adjustable PWM and smooth dimming curve, this fixture is perfectly suited for film and studio applications as well as for creating high-energy effects at concerts and live events.

- Features four 100 W warm white COB LEDs delivering a powerful 3096 K blinder effect.
- Provides individual manual pan control of $\pm 24^\circ$ for each pod to precisely direct light output.
- Offers a 0 to 30 Hz strobe rate and four selectable dim modes for versatile effects.
- Supports multiple DMX channel profiles (1, 3, 4, or 9) for flexible control integration.
- Features adjustable Pulse Width Modulation (PWM) to eliminate flicker in broadcast applications.
- Allows power linking for up to 10 units at 230 V to simplify rigging and cabling.



SPECIFICATIONS

Optical

Light Source: 4 LEDs (WW) 100 W, (2.3 A), 3096 K, 50,000 hours life expectancy

Color Temperature (at full): 3096 K

Beam Angle: 49°

Field Angle: 79°

Illuminance (total): 999 lux @ 5 m

Illuminance (per cell): 242 lux @ 5 m

Pixels: 2 x 2

Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 25,000 Hz

Dynamic Effects

Pan: $\pm 24^\circ$ manual adjustment per pod

Dimmer: Electronic

Shutter/Strobe: Electronic

Strobe Rate: 0 to 30 Hz

Standalone Color Mixing: Yes

Dim Modes: 4

Built-in Automated Programs: Yes

Construction / Physical

Dimensions: 14.2 x 6.4 x 14.2 in (362 x 163 x 362 mm)

Weight: 19 lb (8.7 kg)

Exterior Color: Black

Housing Material: Aluminum die-cast

Connections

Power Connection: Edison (Local) plug to Neutrik powerCON

Power Input: Neutrik powerCON

Power Output: Neutrik powerCON

Data Connectors: 5-pin XLR

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX

DMX Channels: 1, 3, 4 or 9

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 5 units @ 120 V; 9 units @ 208 V; 10 units @ 230 V

Power and Current: 301 W, 2.49 A @ 120 V, 60 Hz

Power and Current: 287 W, 1.43 A @ 208 V, 60 Hz

Power and Current: 286 W, 1.29 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE

IP Rating: IP20, dry location

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Safety Cable: SC-07

Neutrik powerCON cables

DMX Cables

What's Included

STRIKE 4

Neutrik powerCON power cord