

## STRIKE Array 2

An IP65-rated audience blinder with two intense, independently focusable warm white LED pods that emulate a classic tungsten-style amber shift when dimming. Perfect for broadcast applications, tours, and outdoor festivals that require a high-quality, scalable, and weather-resistant lighting fixture with a tool-free interlocking system.



- Features a high CRI of 92.9 and adjustable PWM for flicker-free, broadcast-ready performance.
- Offers precise directional control with two independently adjustable pan and tilt pods.
- Achieves exceptionally smooth fades and dimming with high-resolution 16-bit control.
- Build large, scalable arrays quickly using the innovative tool-free interlocking system.
- Supports both DMX and RDM protocols for flexible control and remote fixture management.
- Streamlines rigging with Omega-Bracket locks and multiple mounting locations for versatile setup.

### SPECIFICATIONS

#### Optical

**Light Source:** 96 LED (WW) 1.33 W, (2.2 A), 2700 K, 50,000 hours life expectancy

**Light Source:** 10 LED (Amber) 2.63 W, (.750 A), 50,000 hours life expectancy

**Color Temperature (at full):** 2792 K

**CRI:** 92.9

**TLCI:** 91

**Beam Angle:** 60.3°

**Field Angle:** 99°

**Illuminance (total):** 360 lux @ 5 m

**Selectable PWM:** 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 25,000 Hz

#### Dynamic Effects

**Dimmer:** Electronic

**Strobe Rate:** 0 to 25 Hz

**Dim Modes:** 4

**Built-in Automated Programs:** Yes

#### Construction / Physical

**Dimensions:** 18.5 x 10.4 x 6.3 in (469 x 264.5 x 161 mm)

**Dimensions (shipping size):** 20.7 x 8.5 x 12.8 in (525 x 215 x 325 mm)

**Weight:** 17.6 lb (8 kg)

**Weight (shipping weight):** 21.6 lb (9.8 kg)

**Exterior Color:** Black

**Housing Material:** Aluminum die-cast

#### Connections

**Power Connection:** Edison (Local) plug to Seetronic Powerkon IP65

**Power Input:** Seetronic Powerkon IP65

**Power Output:** Seetronic Powerkon IP65

**Data Connectors:** 5-pin IP65 XLR

**Cable Length (power):** 5 ft (1.5 m)

#### Control

**Control Protocol:** DMX, RDM

**DMX Channels:** 1, 2, 3, 4, 5, 8 or 9

#### Electrical

**Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)

**Power Linking:** 11 units @ 100 V; 13 units @ 120 V; 22 units @ 208 V; 24 units @ 230 V; 25 units @ 240 V

**Power and Current:** 124 W, 1.24 A @ 100 V, 60 Hz [3.1 A inrush]

**Power and Current:** 123 W, 1.04 A @ 120 V, 60 Hz [1.8 A inrush]

**Power and Current:** 127 W, 0.61 A @ 208 V, 60 Hz [1.9 A inrush]

**Power and Current:** 129 W, 0.56 A @ 230 V, 50 Hz [3.8 A inrush]

**Power and Current:** 130 W, 0.54 A @ 240 V, 50 Hz [1.2 A inrush]

**Power and Current (resting):** 3 W, .021 A @ 100 V, 60 Hz

**Power and Current (resting):** 4 W, .029 A @ 120 V, 60 Hz

**Power and Current (resting):** 7 W, .040 A @ 208 V, 60 Hz

**Power and Current (resting):** 9 W, .040 A @ 230 V, 50 Hz

**Power and Current (resting):** 10 W, .044 A @ 240 V, 50 Hz

## Certifications / Qualifications

**Certifications:** CE, MET

**IP Rating:** IP65, temporary outdoor/wet use, with pressure equalizing M12 GORE valve

**Temperature (Ambient):** -4 °F to 113 °F (-20 °C to 45 °C)

## Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Seetronic Powerkon power linking cables

5-pin IP or Non-IP DMX Cables

STRIKE Array Flush Bracket

## What's Included

STRIKE Array 2

Seetronic Powerkon IP65

Omega bracket with mounting hardware

Warranty Card

Quick Reference Guide or User Manual