



STRIKE Array 4C

An IP65-rated audience blinder with four independently focusable pods, delivering a full spectrum of color and a wide range of whites via its RGBA-WW LEDs, complete with smooth low-end dimming and a classic tungsten-emulating Red Shift.

Its high CRI, variable PWM, and scalable, weather-resistant design make it the ideal blinder for broadcast studios, outdoor festivals, concert tours, and large-scale productions.

- Features a high CRI of 94.6 at 3200K for superior color rendering on camera.
- Provides broad, even coverage with a 59.6° beam angle and 102.2° field angle.
- Offers precise intensity control with ultra-smooth 18-bit dimming and four dim modes.
- A proprietary tool-free interlocking system enables fast, scalable unit configuration.
- Supports DMX, RDM, Art-Net, and sACN for flexible, comprehensive control options.
- Allows for independent strobe control on each pod to create dynamic, high-impact effects.

SPECIFICATIONS

Optical

Light Source: 268 LEDs (112 quad-color RGBA, 156 WW), 2.7W to 4.32 W, (871 mA), 50,000 hours life expectancy.

Color Temperature (range): 2800 to 6500 K

Color Temperature (at full): 5991 K

CRI (@3200K): 94.6

Beam Angle: 59.6°

Field Angle: 102.2°

Lumens: 53,481

Illuminance: 1979 lux @ 5 m

Selectable PWM: 600Hz, 1200Hz, 2000Hz, 4000Hz, 6000Hz, 25000Hz

Dynamic Effects

Dimmer: Electronic

Shutter/Strobe: Electronic

Strobe Rate: 0 to 30 Hz

Standalone Color Mixing: Yes

Color Temperature Presets: Yes

Dim Modes: 4

Dim Curves: 4

Built-in Automated Programs: Yes

Construction / Physical

Dimensions: 19.17 x 16.70 x 6.45 in (487.02 x 424.21 x 163.84 mm)

Weight: 34.4 lb (15.4 kg)

Exterior Color: Black

Housing Material: Magnesium alloy

Connections

Power Connection: Edison (Local) plug to Seetronic Powerkon IP65

Power Input: Seetronic Powerkon IP65

Data Connectors: 5-pin Seetronic IP65 XLR or Seetronic IP65 etherCON

Cable Length (power): 5 ft (1.5 m)

Software Update: USB-C

Control

Control Protocol: Art-Net, sACN, DMX ,RDM

Modes/Personalities: 10 personalities (1, 3, 5, 7, 10, 12, 13, 16, 22 or HSV)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power and Current: 1180 W, 9.92 A @ 120 V, 60 Hz

Power and Current: 1150 W, 5.60 A @ 208 V, 60 Hz

Power and Current: 1140 W, 5.02 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET, FCC, ETL, cULus,

IP Rating: IP65, outdoor/wet, with pressure equalizing M12 GORE valve

Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

Optional Accessories

STRIKE Array Flush Bracket

Professional Clamps: CTC-50HC, CTC-50HCN

Safety Cable: SC-08

IP Rated Seetronic® Powerkon Extensions

IP Rated DMX cables

IP Rated EtherCon Cables

UPLOAD 03 software uploader

What's Included

STRIKE Array 4C

Seetronic Powerkon IP65

Omega bracket with mounting hardware