

STRIKE Saber 10

An IP65-rated, ten-cell pixel-mappable batten that delivers the warm, golden glow of classic tungsten with emulated red-shift dimming and versatile blinder, strobe, and wash effects.

Its tour-ready, weatherproof design makes it ideal for large-scale concerts, broadcast studios, and theatrical stages where a versatile blinder, wash, or footlight is needed.

- Delivers a high-quality 2792 K warm white with an excellent CRI of 92.9.
- Provides individual pixel-mappable control over all ten cells for advanced visual effects.
- Projects a tight 20.9-degree beam angle for focused wash or blinder applications.
- Features a fast, tool-free interlocking system for quick end-to-end assembly of multiple units.
- Offers versatile control via DMX and RDM with multiple channel personalities.
- Includes adjustable Pulse Width Modulation (PWM) for flicker-free operation on camera.



SPECIFICATIONS

Optical

Color Temperature (at full): 2792 K

CRI: 92.9

TLCI: 91

Beam Angle vertical: 20.9

Beam Angle horizontal: 20.9

Field Angle vertical: 25.1

Field Angle horizontal: 25.1

Lumens: 5,959

Illuminance: 1686 lux @ 5 m

Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

Connections

Power Connection: Edison (Local) plug to Seetronic Tru1

Power Input: Seetronic Tru1

Power Output: Seetronic Tru1

Data Connectors: 5-pin XLR

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX, RDM

DMX Channels: 1, 3, 6, 13, 22, 26Ch1 or 26Ch2

Modes/Personalities: 6 personalities (1Ch, 3Ch, 6Ch, 13Ch, 22Ch, 26Ch1, 26Ch2)

Dynamic Effects

Dimmer: Electronic

Strobe: Electronic

Strobe Rate: 0 to 26.7 Hz

Dim Modes: 4

Built-in Automated Programs: Yes

Construction / Physical

Dimensions: 39.3 x 3.08 x 6.18 in (1000 x 78.4 x 157 mm)

Weight: 14.6 lb. (8 kg)

Exterior Color: Black

Housing Material: Aluminum alloy, Aluminum die-cast

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 6 units @ 110 V; 16 units @ 208 V; 1 units @ 230 V

Power and Current: 183 W, 1.83 A @ 100 V, 60 Hz

Power and Current: 181 W, 1.52 A @ 120 V, 60 Hz

Power and Current: 178 W, .86 A @ 208 V, 60 Hz

Power and Current: 177 W, .78 A @ 230 V, 50 Hz

Power and Current: 178 W, .75 A @ 240 V, 60 Hz

Certifications / Qualifications

Certifications: CE, MET

IP Rating: IP65

Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Seetronic Powerkon power linking cables

5-pin DMX Cables

What's Included

STRIKE Saber

Seetronic Powerkon – Bare Wire