

WELL Batten 14 – 15° Filter Pack

A four-pack of 15-degree filters designed as a slide-in lens option to shape the light beam of the WELL Batten 14.

Perfect for quickly modifying the fixture's wide wash for applications requiring a narrower, more focused beam of light.

- Widens the native 17.3° beam angle of the WELL Batten 14 fixture to 32.8°.
- Features a simple slide-in design for quick installation and removal on site.
- Creates a wider, softer wash ideal for large area or short-throw coverage.
- Includes a single notch for instant visual identification of the beam angle.
- Designed with a compact size for easy storage within the fixture's charging case.
- Ships as a convenient four-piece pack to outfit multiple fixtures at once.



SPECIFICATIONS

Optical	Construction / Physical
Beam Angle: 17.3°	Dimensions: 38.91 x 1.84 in (104 x 104mm)
Field Angle: 32.8°	Weight: 0.06 lb (0.03kg)
Illuminance: 507 lux @ 5 m (AC)	Certifications / Qualifications
Lumens: 171 (AC)	Certifications: CE
Illuminance: 504 lux @ 5 m (Battery curve off)	IP Rating: IP65, temporary outdoor/wet use
Lumens: 1698 (Battery curve off)	What's Included
Illuminance: 491 lux @ 5 m (5 hr)	WELL Batten 14 15° Filter X4
Lumens: 1655 (5 hr)	
Illuminance: 321 lux @ 5 m (8 hr)	
Lumens: 1081 (8 hr)	
Illuminance: 213 lux @ 5 m (12 hr)	
Lumens: 717 (12 hr)	
Illuminance: 142 lux @ 5 m (18 hr)	
Lumens: 476 (18 hr)	