

WELL Batten 14 – 60° x 10° Filter Pack

A four-piece pack of 60° x 10° elliptical filters designed as a slide-in lens option for the WELL Batten 14.

Ideally suited for creating a wide, linear wash of light to evenly illuminate walls, cycloramas, and other scenic or architectural elements.

- Widens the native 16° beam angle to an elliptical 25° x 42.8° wash.
- Offers simple, tool-free installation for rapid on-site beam adjustments.
- Features a flexible construction for convenient, compact storage and transport.
- A distinct double notch allows for immediate identification of the filter's beam angle.
- Sold as a pack of four to consistently outfit multiple fixtures on a project.
- Modifies the output to deliver 3,007 lumens of smooth, wide coverage.



SPECIFICATIONS

Optical

Beam Angle: 25 X 42.8°

Illuminance: 216 lux @ 5 m (AC)

Lumens: 3007 (AC)

Illuminance: 123 lux @ 5 m (Battery curve off)

Lumens: 1691 (Battery curve off)

Illuminance: 131 lux @ 5 m (5 hr)

Lumens: 1789 (5 hr)

Illuminance: 79 lux @ 5 m (8 hr)

Lumens: 1105(8 hr)

Illuminance: 50 lux @ 5 m(12 hr)

Lumens: 687 (12 hr)

Illuminance: 30 lux @ 5 m (18 hr)

Lumens: 428 (18 hr)

Construction / Physical

Dimensions: 38.91 x 1.84 in (988.5 x 46.9mm)

Weight: 0.06 lb (0.03kg)

Certifications / Qualifications

Certifications: CE

IP Rating: IP65, temporary outdoor/wet use

What's Included

WELL Batten 14 60x10° Filter x4