

## WELL Batten 14 – 60° x 10° Filter Pack

A four-piece pack of 60° x 10° elliptical filters designed as a slide-in lens option for the WELL Batten 14.

Ideally suited for creating a wide, linear wash of light to evenly illuminate walls, cycloramas, and other scenic or architectural elements.

- Widens the native 16° beam angle to an elliptical 25° x 42.8° wash.
- Offers simple, tool-free installation for rapid on-site beam adjustments.
- Features a flexible construction for convenient, compact storage and transport.
- A distinct double notch allows for immediate identification of the filter's beam angle.
- Sold as a pack of four to consistently outfit multiple fixtures on a project.
- Modifies the output to deliver 3,007 lumens of smooth, wide coverage.



### SPECIFICATIONS

#### Optical

**Beam Angle:** 25 X 42.8°

**Illuminance:** 216 lux @ 5 m (AC)

**Lumens:** 3007 (AC)

**Illuminance:** 123 lux @ 5 m (Battery curve off)

**Lumens:** 1691 (Battery curve off)

**Illuminance:** 131 lux @ 5 m (5 hr)

**Lumens:** 1789 (5 hr)

**Illuminance:** 79 lux @ 5 m (8 hr)

**Lumens:** 1105 (8 hr)

**Illuminance:** 50 lux @ 5 m (12 hr)

**Lumens:** 687 (12 hr)

**Illuminance:** 30 lux @ 5 m (18 hr)

**Lumens:** 428 (18 hr)

#### Construction / Physical

**Dimensions:** 38.91 x 1.84 in (988.5 x 46.9mm)

**Weight:** 0.06 lb (0.03kg)

#### Certifications / Qualifications

**Certifications:** CE

**IP Rating:** IP65, temporary outdoor/wet use

#### What's Included

WELL Batten 14 60x10° Filter x4