



WELL FIT

A compact, high-powered, battery-operated LED wash light featuring a reflective chrome housing and multiple wireless control options for sophisticated uplighting. Perfect for corporate events, weddings, and upscale venues where quick, cable-free setup and an unobtrusive fixture design are essential.

- Houses four 10W quad-color RGBA LEDs for rich, saturated color mixing.
- Provides up to 8 hours of continuous operation from a single five-hour charge.
- Built with a rugged IP65-rated housing for reliable performance in any weather.
- Supports versatile control via W-DMX, an included IR remote, or onboard display.
- Produces a tight 10.8° beam angle for creating sharp, defined uplighting effects.
- Ships in a 6-unit charging road case for streamlined transport and recharging.

SPECIFICATIONS

Optical

Light Source: 4 LEDs (quad- color RGBA) 10 W, (720 mA), 50,000 hours life expectancy).

Beam Angle: 10.8°

Field Angle: 19.6°

Illuminance (19.6°): 988 lux @ 5 m

PWM Frequency: 1200 Hz

Dynamic Effects

Color Macros: 5 macros

Dimmer: Electronic

Shutter/Strobe: Electronic

Strobe Rate: 0 to 24 Hz

Standalone Color Mixing: Yes

Color Temperature Presets: Yes

Dim Modes: 4

Built-in Automated Programs: Yes

Construction / Physical

Dimensions: 5.4 x 5.7 x 8 in (138 x 145 x 202 mm)

Dimensions (charging case): 20.4 x 18.5 x 21.2 in (519 x 470 x 540 mm)

Weight (charging case): 103.6 lb (47 kg)

Exterior Color: Chrome

Housing Material: Aluminum die-cast

Connections

Power Connection: Edison (Local) plug to Neutrik® powerCON

Power Input: Neutrik® powerCON®

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: W-DMX™, IRC

DMX Channels: 3, 4, 6 or 10

Modes/Personalities: 5 personalities (4Ch, 6Ch, 10Ch, HSV, HSI)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 4 units @ 120 V; 7 units @ 208 V; 8 units @ 230 V

Power and Current (single unit charging): 60 W, 0.641 A @ 100 V, 60 Hz

Power and Current (charging case): 345 W, 3.323 A @ 100 V, 60 Hz

Power and Current (single unit charging): 58 W, 0.535 A @ 120 V, 60 Hz

Power and Current (charging case): 334 W, 2.750 A @ 120 V, 60 Hz

Power and Current (single unit charging): 51 W, 0.363 A @ 208 V, 60 Hz

Power and Current (charging case): 322 W, 1.584 A @ 208 V, 60 Hz

Power and Current (single unit charging): 54 W, 0.342 A @ 230 V, 50 Hz

Power and Current (charging case): 317 W, 1.422 A @ 230 V, 50 Hz

Power and Current (single unit charging): 54 W, 0.335 A @ 240 V, 50 Hz

Power and Current (charging case): 311 W, 1.363 A @ 240 V, 50 Hz

Battery

Battery type: Lithium Ion

Rechargeable: Yes

Battery Charge Time: 5 hours

Battery Life: (all on) 8 hours, (single LED) 20 hours

Battery Power: 14.8 V, 11 Ah

Certifications / Qualifications

Certifications: CE, UKCA

IP Rating: IP65, temporary outdoor/wet use

Optional Accessories

Clamps

WDMX MicroT-1 TRX G6

What's Included

- (6) WELL FIT
- (1) Charging case
- (1) IR remote
- (1) powerCON power cable with Edison plug
- (1) QRG
- (1) Warranty card