

WELL Gobo



A compact, battery-powered, and outdoor-ready gobo projector featuring a manual zoom and framing shutters for projecting precise images from both glass and metal gobos.

Ideal for corporate and event rental inventories requiring a fast-deploying, weather-resistant, and wireless solution for projecting custom branding and patterns in any indoor or outdoor setting.

- Features a 25.2 W cool white LED source delivering crisp 6542 K gobo projection.
- Integrated manual framing shutters enable precise beam shaping for flawless shutter cuts.
- A built-in rechargeable battery delivers up to 8 hours of completely wireless operation.
- Offers flexible control via W-DMX, an included IR remote, or the onboard OLED display.
- Accepts both standard metal and glass E size gobos up to 1 mm thick.
- Includes four units in a power-linking, self-charging case for efficient deployment.

SPECIFICATIONS

Optical

Light Source: 1 LED (CW) 25.2 W, (1.3 A), 6542 K, 50,000 hours life expectancy.

Color Temperature (at full): 6542 K

Lumens: 2892

CRI: 79.1

Beam Angle: 17.3° to 36.6°

Field Angle: 20° to 41°

Zoom Angle: 20° to 41°

Illuminance (17.3°): 1,487 lux @ 5 m

Illuminance (8 hr mode 17.3°): 1,487 lux @ 5 m

Illuminance (36°): 347 lux @ 5 m

Illuminance (P/S mode 36°): 165 lux @ 5 m

Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

Dynamic Effects

Manual Tilt: 180°

Tilt Ranges: 0° to 180° tilt

Dimmer: Electronic

Shutter/Strobe: Electronic

Zoom: Manual

Focus: Manual

Strobe Rate: 0 to 25 Hz

Dim Modes: 4

Built-in Automated Programs: Yes

Construction / Physical

Dimensions (Single Unit): 10.11 x 6.81 x 12 in (257 x 173 x 305 mm)

Dimension (Charging Case): 27.64 x 17.24 x 23.36 in (702mm x 438 x 593.4 mm)

Weight (Single Unit): 6.6 lb (3 kg)

Weight (Charging Case): 71 lb (32.21 kg)

Exterior Color: Black

Housing Material (Single Unit): Aluminum diecast

Housing Material (Charging Case): Aluminum alloy, wood

Gobo Size (Optional): "E": 37.5 mm (outside), 24 mm (image), 1 mm (max. thickness)

Connections

Power Connection: Edison (Local) plug to Seetronic Powerkon

Power Input: Seetronic Powerkon

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: W-DMX, IRC

DMX Channels: 1, 2, 3 or 6

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 8 units @ 120 V; 16 units @ 208 V; 18 units @ 230 V

Power and Current (single unit charging): 42 W, 0.436 A @ 100 V, 60 Hz

Power and Current (charging case): 153 W, 1.537 A @ 100 V, 60 Hz

Power and Current (single unit charging): 42 W, 0.362 A @ 120 V, 60 Hz

Power and Current (charging case): 153 W, 1.386 A @ 120 V, 60 Hz

Power and Current (single unit charging): 38 W, 0.220 A @ 208 V, 60 Hz

Power and Current (charging case): 147 W, 0.719 A @ 208 V, 60 Hz

Power and Current (single unit charging): 40 W, 0.215 A @ 230 V, 50 Hz

Power and Current (charging case): 144 W, 0.663 A @ 230 V, 50 Hz

Power and Current (single unit charging): 39 W, 0.211 A @ 240 V, 50 Hz

Power and Current (charging case): 143 W, 0.629 A @ 240 V, 50 Hz

Battery

Battery type: Lithium Ion

Rechargeable: Yes

Battery Charge Time: 8 hours

Battery Life: 5 hrs (high output), 8 (power saving mode)

Battery Power: 29.6, 4400 mAh

Certifications / Qualifications

Certifications: CE, UKCA

IP Rating: IP65, temporary outdoor/wet use

What's Included

(4) WELL Gobo
Charging Case
powerCON power cable with Edison plug
(4) Gobo holder