

WELL Pad



A completely wireless, battery-powered, and outdoor-ready RGBA LED wash light featuring a wide beam, versatile control options, and a unique rotating base for broad surface coverage.

Ideal for uplighting walls, landscapes, and architectural elements in any indoor or outdoor setting where a completely cable-free setup is required.

- Features 96 RGBA LEDs for rich color mixing and vibrant, even washes.
- Includes a magnetic diffuser filter to soften and widen the beam for broad applications.
- Built with an IP65-rated housing for reliable performance in temporary outdoor settings.
- Offers a unique 90-degree rotating lighting panel for precise aiming and versatile coverage.
- Delivers up to 9 hours of operation at full output on a single 6-hour charge.
- Supports W-DMX control and selectable PWM for flicker-free, on-camera operation.

SPECIFICATIONS

Optical

Light Source: 96 LEDs (24 red, 24 green, 24 blue, 24 amber) 1 to 3 W, (500 mA), 50,000 hours life expectancy

Beam Angle (w/o filter): 22°

Beam Angle (w/filter): 27°

Field Angle (w/o filter): 38°

Field Angle (w/filter): 51°

Illuminance (w/o filter): 553 lux @ 5 m

Illuminance (w/filter): 316 lux @ 5 m

Dynamic Effects

Tilt: 90°

Tilt Ranges: 0° to 90° tilt

Color Macros: 5 macros

Dimmer: Electronic

Shutter/Strobe: Electronic

Strobe Rate: 0 to 25 Hz

Standalone Color Mixing: Yes

Color Temperature Presets: Yes

Dim Modes: 4

Built-in Automated Programs: Yes

Construction / Physical

Dimensions: 15.98 x 8.38 x 3.99 in (406 x 213 x 101.5 mm)

Dimensions (charging case): 26.29 x 22.83 x 19 in (668 x 580 x 482.6 mm)

Weight (single unit): 21.6 lb (9.8kg)

Weight (charging case): 67.8 lb (30.8kg)

Exterior Color: Black

Housing Material: Aluminum die-cast

Connections

Power Connection: Edison (Local) plug to Neutrik powerCON (ROAD CASE ONLY)

Power Input: Neutrik powerCON

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: W-DMX

DMX Channels: 4, 6 or 10

Modes/Personalities: 3 personalities (4Ch, 6Ch, 10Ch)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power and Current (single unit charging): 120 W, 0.996 A @ 120 V, 60 Hz

Power and Current (charging case): 480 W, 3.984 A @ 120 V, 60 Hz

Power and Current (single unit charging): 135 W, 0.654 A @ 208 V, 60 Hz

Power and Current (charging case): 540 W, 2.616 A @ 208 V, 60 Hz

Power and Current (single unit charging): 137 W, 0.594 A @ 230 V, 50 Hz

Power and Current (charging case): 548 W, 2.376 A @ 230 V, 50 Hz

Battery

Battery type: Lithium Ion

Rechargeable: Yes (Inside road case)

Battery Charge Time: 6 hours

Battery Life: (all on) 9 hours, (single LED) 13 hours

Battery Power: 18.5 V, 26 Ah

Certifications / Qualifications

Certifications: CE

IP Rating: IP65, temporary outdoor/wet use with pressure equalizing M12 GORE valve

Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Safety Cable: SC-07

What's Included

WELL Pad X4

Charging case

IR remote

(4) Diffusion filters

powerCON power cable with Edison plug