

## WELL POD 2



A compact, battery-powered PAR wash light offering high output, excellent color rendering, and flexible mounting with a removable split-yoke design. Ideal for rental inventory and lighting professionals requiring a fast, flexible wash lighting solution for any indoor or outdoor production where quick setup is crucial.

- Features seven RGBWW LEDs for rich colors and high-quality whites from 2800K to 6500K.
- Offers multiple battery runtime selections, delivering up to 18 hours of continuous operation.
- Built with a rugged, IP65-rated housing for reliable performance in any outdoor environment.
- Provides versatile control options including DMX, CRMX, RDM, RF, and mobile app support.
- Sold as a six-unit kit in a road case that charges all fixtures with the lid closed.
- Includes adjustable PWM settings to ensure flicker-free output for on-camera applications.

### SPECIFICATIONS

#### Optical

**Light Source:** 7 LEDs (RGBWW) 13.2 W, (556 mA), 50,000 hours life expectancy

**Color Temperature (range):** 2800 to 6500 K

**Beam Angle:** 11.5°

**Field Angle:** 21.6°

**Cutoff Angle:** 36.9°

**Lumens:** 1797 lm (AC power)

**Illuminance:** lux 1089 @ 5 m (AC power)

**Lumens:** 718 lm (OFF battery setting)

**Illuminance:** 436 lux @ 5 m (OFF battery setting)

**Lumens:** 834 lm (5-hour battery setting)

**Illuminance:** 507 lux @ 5 m (5-hour battery setting)

**Lumens:** 528 lm (8-hour battery setting)

**Illuminance:** 319 lux @ 5 m (8-hour battery setting)

**Lumens:** 335 lm (12-hour battery setting)

**Illuminance:** 202 lux @ 5 m (12-hour battery setting)

**Lumens:** 214 lm (18-hour battery setting)

**Illuminance:** 129 lux @ 5 m (18-hour battery setting)

**Selectable PWM:** 600 Hz, 1,200 Hz, 2,000 Hz, 4000 Hz, 6,000 Hz, 25000 Hz

#### Dynamic Effects

**Dimmer:** Electronic

**Shutter/Strobe:** Electronic

**Strobe Rate:** 1 to 30 Hz

**Standalone Color Mixing:** Yes

**Color Temperature Presets:** Yes

**Dim Modes:** 4

**Dim Curves:** 4

**Built-in Automated Programs:** Yes

**Customizable Programs:** No

**Recall Custom Programs:** No

#### Construction / Physical

**Dimensions:** 8.11 x 5.31 x 8.76 in (206 x 138 x 222.5 mm)

**Dimensions (w/o bracket):** 5.43 x 5.43 x 5.67 in (138 x 138 x 144 mm)

**Dimensions case:** 32.7 x 19.3 x 15.4 in (832 x 492 x 390mm)

**Weight:** 7.2 lb (3.3 kg)

**Weight (shipping weight):** 113.8 lb (51.6 kg)

**Exterior Color:** Black

**Housing Material:** Aluminum die-cast

## Connections

**Power Connection:** Edison (local) plug to Seetronic PowerKon IP65

**Power Input (fixture and charging case):** Seetronic PowerKon IP65

**Power Output (fixture and charging case):** Seetronic PowerKon IP65

**Data Connectors:** 5-pin XLR

**Cable Length (power):** 5 ft (1.5 m)

**Software Connection:** USB-C

## Control

**Control Protocol:** RDM, CRMX, NFC, RF

**DMX Channels:** 5, 8, or 12

**Modes/Personalities:** 3 personalities (5Ch, 8Ch, 12Ch)

**Wireless WDMX "G" Compatibility:** G4S

**Wireless Lumen Radio Compatibility:** CRMX

## Electrical

**Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)

### Single unit:

**Power Linking:** 34 units @ 120 V

**Power Linking:** 52 units @ 208 V

**Power Linking:** 54 units @ 230 V

**Power and Current:** 43 W, .35 A @ 120 V, 60 Hz

**Power and Current:** 47 W, .23 A @ 208 V, 60 Hz

**Power and Current:** 45 W, .22 A @ 230 V, 50 Hz

### 6 Pack case:

**Power Linking:** 4 units @ 120 V

**Power Linking:** 6 units @ 208 V

**Power Linking:** 6 units @ 230 V

**Power and Current:** 191 W, 2.75 A @ 120 V, 60 Hz

**Power and Current:** 185 W, 1.96 A @ 208 V, 60 Hz

**Power and Current:** 183 W, 1.76 A @ 230 V, 50 Hz

**6 Pack case fuse:** 4 hours (all fixtures in case)

## Battery

**Battery type:** Lithium Ion

**Rechargeable:** Yes

**Battery Charge Time:** 2 hours

**Battery Life:** 12 hours

**Battery Power:** 25.9 V, 2.5 Ah

## Certifications / Qualifications

**Certifications:** CE, UKCA, FCC, ROHS

**IP Rating:** IP65, temporary outdoor/wet use

**Temperature (Ambient):** -4 °F to 113 °F (-20 °C to 45 °C)

## Optional Accessories

Clamps

WELL POD 2 - 15° Filter Pack

WELL POD 2 60° x 10° Filter Pack

WELL POD 2 White Fixture Cover

PowerKon Extension cables

5 pin DMX Cables

W-DMX Micro T-1 TRX G6

## What's Included

(6) WELL POD 2

(1) 6 slot charging case

(6) detachable split yokes

(1) RF controller

(1) QRG