

## Well Panel / Panel X – 100° Hard Filter



This rigid, magnetic filter instantly attaches to WELL Panel fixtures, transforming the native beam into an expansive and even 90.7° wash for broad coverage.

Its durable, IP65-rated design and compact size make it an essential tool for dynamic, on-the-fly adjustments in demanding outdoor event production environments.

- Easily install and widen the beam angle of the WELL Panel X from 11.6° to 90.7°
- Small size makes storage in charging case simple
- Simple installation and removal for on-site application
- Easily identifiable numbering for beam angle identification
- Rigid substrate lens is ideal for outdoor applications
- Ships as a single filter

### SPECIFICATIONS

#### Optical

**Beam Angle:** 90.7°

**Field Angle:** 126.3

**Illuminance:** 128 lux @ 5 m (AC)

**Lumens:** 6230 (AC)

**Illuminance:** 127 lux @ 5 m (Battery curve off)

**Lumens:** 6158 (Battery curve off)

**Illuminance:** 53 lux @ 5 m (5 hr)

**Lumens:** 2626 (5 hr)

**Illuminance:** 33 lux @ 5 m (8 hr)

**Lumens:** 1599 (8 hr)

**Illuminance:** 22 lux @ 5 m (12 hr)

**Lumens:** 1051 (12 hr)

**Illuminance:** 16 lux @ 5 m (18 hr)

**Lumens:** 75(18 hr)

#### Construction / Physical

**Dimensions:** 4.33 in dia. (336 x 123 x 10 mm)

**Weight:** 0.6 lb (0.3kg)

#### Certifications / Qualifications

**Certifications:** CE

**IP Rating:** IP65, temporary outdoor/wet use

#### What's Included

WELL Panel X 100° Filter

Safety cable