

Well Panel / Panel X – 100° Hard Filter



This rigid, magnetic filter instantly attaches to WELL Panel fixtures, transforming the native beam into an expansive and even 90.7° wash for broad coverage.

Its durable, IP65-rated design and compact size make it an essential tool for dynamic, on-the-fly adjustments in demanding outdoor event production environments.

- Easily install and widen the beam angle of the WELL Panel X from 11.6° to 90.7°
- Small size makes storage in charging case simple
- Simple installation and removal for on-site application
- Easily identifiable numbering for beam angle identification
- Rigid substrate lens is ideal for outdoor applications
- Ships as a single filter

SPECIFICATIONS

Optical

Beam Angle: 90.7°

Field Angle: 126.3

Illuminance:

AC: 128 lux @ 5 m

Battery curve off: 127 lux @ 5 m

5 hr: 53 lux @ 5 m

8 hr: 33 lux @ 5 m

12 hr: 22 lux @ 5 m

18 hr: 16 lux @ 5 m

Lumens:

AC: 6230

Battery curve off: 6158

5 hr: 2626

8 hr: 1599

12 hr: 1051

18 hr: 75

Construction / Physical

Dimensions: 4.33 in dia. (336 x 123 x 10 mm)

Weight: 0.6 lb (0.3kg)

Certifications / Qualifications

Certifications: CE

IP Rating: IP65, temporary outdoor/wet use

What's Included

WELL Panel X 100° Filter

Safety cable