

## Well Panel / Panel X – 30° x 60° Hard Filter

A rigid, magnetically attached lens option that widens the beam angle of the WELL Panel X for broader, more asymmetrical coverage.

Its durable substrate is perfect for outdoor long-throw applications, such as illuminating trees or creating smooth, linear washes on architectural surfaces.

- Easily install and widen the beam angle of the WELL Panel X from 11.6° to 41.9 x 72.7°
- Small size makes storage in charging case simple
- Ideal for long throw applications for tree lighting
- Simple installation and removal for on-site application
- Easily identifiable numbering for beam angle identification
- Rigid substrate lens is ideal for outdoor applications
- Ships as a single filter



### SPECIFICATIONS

Optical	Construction / Physical
<b>Beam Angle:</b> 41.9 x 72.7°	<b>Dimensions:</b> 4.33 in dia. (336 x 123 x 10 mm)
<b>Cut off Angle:</b> 100.8°	<b>Weight:</b> 0.6 lb (0.3kg)
<b>Illuminance:</b> 405 lux @ 5 m (AC)	Certifications / Qualifications
<b>Lumens:</b> 6162 (AC)	<b>Certifications:</b> CE
<b>Illuminance:</b> 404 lux @ 5 m (Battery curve off)	<b>IP Rating:</b> IP65, temporary outdoor/wet use
<b>Lumens:</b> 614 (Battery curve off)	What's Included
<b>Illuminance:</b> 174 lux @ 5 m (5 hr)	WELL Panel X 60x30° Filter
<b>Lumens:</b> 2650 (5 hr)	Safety cable
<b>Illuminance:</b> 106 lux @ 5 m (8 hr)	
<b>Lumens:</b> 1608 ( 8 hr)	
<b>Illuminance:</b> 70 lux @ 5 m (12 hr)	
<b>Lumens:</b> 1069 (12 hr)	
<b>Illuminance:</b> 50 lux @ 5 m (18 hr)	
<b>Lumens:</b> 769 (18 hr)	