

Well Panel / Panel X – 45° Hard Filter



This rigid, magnetic filter easily attaches to the WELL Panel X, instantly widening the fixture's narrow beam angle for broader, more even coverage.

Its durable, IP65-rated construction is ideal for quick, on-site adjustments in temporary outdoor installations requiring a wider, softer field of light.

- Easily install and widen the beam angle of the WELL Panel X from 11.6° to 45.3°
- Small size makes storage in charging case simple
- Simple installation and removal for on-site application
- Easily identifiable numbering for beam angle identification
- Rigid substrate lens is ideal for outdoor applications
- Ships as a single filter

SPECIFICATIONS

Optical

Beam Angle: 45.3°

Field Angle: 87.2°

Illuminance: 331 lux @ 5 m (AC)

Lumens: 6189 (AC)

Illuminance: 334 lux @ 5 m (Battery curve off)

Lumens: 6237 (Battery curve off)

Illuminance: 143 lux @ 5 m (5 hr)

Lumens: 2682 (5 hr)

Illuminance: 87 lux @ 5 m (8 hr)

Lumens: 1629 (8 hr)

Illuminance: 57 lux @ 5 m (12 hr)

Lumens: 1075 (12 hr)

Illuminance: 40 lux @ 5 m (18 hr)

Lumens: 762 (18 hr)

Construction / Physical

Dimensions: 4.33 in dia. (336 x 123 x 10 mm)

Weight: 0.6 lb (0.3kg)

Certifications / Qualifications

Certifications: CE

IP Rating: IP65, temporary outdoor/wet use

What's Included

WELL Panel X 45° Filter

Safety cable