# Well Panel / Panel X – 45° Hard Filter

This rigid, magnetic filter easily attaches to the WELL Panel X, instantly widening the fixture's narrow beam angle for broader, more even coverage.

Its durable, IP65-rated construction is ideal for quick, on-site adjustments in temporary outdoor installations requiring a wider, softer field of light.

- Easily install and widen the beam angle of the WELL Panel X from 11.6° to 45.3°
- Small size makes storage in charging case simple
- Simple installation and removal for on-site application
- Easily identifiable numbering for beam angle identification
- Rigid substrate lens is ideal for outdoor applications
- Ships as a single filter

## SPECIFICATIONS

### Optical

**Beam Angle:** 45.3°

**Field Angle:** 87.2°

**Illuminance:** 331 lux @ 5 m (AC)

**Lumens:** 6189 (AC)

**Illuminance:** 334 lux @ 5 m (Battery curve off)

**Lumens:** 6237 (Battery curve off)

**Illuminance:** 143 lux @ 5 m (5 hr)

**Lumens:** 2682 (5 hr)

**Illuminance:** 87 lux @ 5 m (8 hr)

**Lumens:** 1629 ( 8 hr)

**Illuminance:** 57 lux @ 5 m (12 hr)

**Lumens:** 1075 (12 hr)

**Illuminance:** 40 lux @ 5 m (18 hr)

**Lumens:** 762 (18 hr)

### Construction / Physical

**Dimensions:** 4.33 in dia. (336 x 123 x 10 mm)

**Weight:** 0.6 lb (0.3kg)

### Certifications / Qualifications

**Certifications:** CE

**IP Rating:** IP65, temporary outdoor/wet use

### What's Included

WELL Panel X 45° Filter
Safety cable