

Well Panel / Panel X – 10° x 60° Hard Filter

This rigid, magnetic filter easily attaches to widen the beam angle, creating a linear wash effect for long-throw applications and outdoor use.

Designed for fast on-site adjustments, it empowers designers to shape light for architectural details, tree lighting, or dynamic outdoor event backdrops.



- Easily install and widen the beam angle of the WELL Panel X from 11.6° to 27.2 x 51.1°
- Small size makes storage in charging case simple
- Ideal for long throw applications for tree lighting
- Simple installation and removal for on-site application
- Easily identifiable numbering for beam angle identification
- Rigid substrate lens is ideal for outdoor applications
- Ships as a single filter

SPECIFICATIONS

Optical

Beam Angle: 27.2 x 51.1°

Cut off Angle: 74.6°

Illuminance: 783 lux @ 5 m (AC)

Lumens: 6662 (AC)

Illuminance: 793 lux @ 5 m (Battery curve off)

Lumens: 6753 (Battery curve off)

Illuminance: 343 lux @ 5 m (5 hr)

Lumens: 2907 (5 hr)

Illuminance: 210 lux @ 5 m (8 hr)

Lumens: 1840 (8 hr)

Illuminance: 137 lux @ 5 m (12 hr)

Lumens: 1209 (12 hr)

Illuminance: 99 lux @ 5 m (18 hr)

Lumens: 854(18 hr)

Construction / Physical

Dimensions: 4.33 in dia. (336 x 123 x 10 mm)

Weight: 0.6 lb (0.3kg)

Certifications / Qualifications

Certifications: CE

IP Rating: IP65, temporary outdoor/wet use

What's Included

WELL Panel X 60x10° Filter

Safety cable