

WELL POD 2 – 15° Filter Pack

A six-piece pack of 15° filters in magnetic frames designed to quickly and easily modify the beam angle of the WELL POD 2.

Perfectly suited for event applications requiring a quick transformation of a wide wash into a focused beam for accenting decor, architecture, or truss elements.



- Changes the fixture's native 11.5° beam angle to a broader 18.9° wash.
- Attaches instantly via integrated magnetic frames for rapid on-site adjustments.
- Ships as a convenient pack of six filters to outfit multiple fixtures.
- Designed with a single notch on the frame for immediate beam angle identification.
- Compact design allows for convenient storage directly inside the fixture's charging case.
- Delivers a bright, even field of 311 lux at 5 meters with the filter installed.

SPECIFICATIONS

Optical

Beam Angle: 18.9°

Field Angle: 37.3°

Illuminance: 311 lux @ 5 m (AC)

Lumens: 1254 (AC)

Illuminance: 125 lux @ 5 m (Battery curve off)

Lumens: 503 (Battery curve off)

Illuminance: 145 lux @ 5 m (5 hr)

Lumens: 588 (5 hr)

Illuminance: 91 lux @ 5 m (8 hr)

Lumens: 372 (8 hr)

Illuminance: 58 lux @ 5 m (12 hr)

Lumens: 235 (12 hr)

Illuminance: 37 lux @ 5 m (18 hr)

Lumens: 150 (18 hr)

Construction / Physical

Dimensions: 4.33 in dia. (110 mm dia)

Weight: 0.05 lb (0.025kg)

Certifications / Qualifications

Certifications: CE

IP Rating: IP65, temporary outdoor/wet use

What's Included

WELL POD 2 15° Filter X 6