

## WELL POD 2 – 15° Filter Pack



A six-piece pack of 15° filters in magnetic frames designed to quickly and easily modify the beam angle of the WELL POD 2.

Perfectly suited for event applications requiring a quick transformation of a wide wash into a focused beam for accenting decor, architecture, or truss elements.

- Changes the fixture's native 11.5° beam angle to a broader 18.9° wash.
- Attaches instantly via integrated magnetic frames for rapid on-site adjustments.
- Ships as a convenient pack of six filters to outfit multiple fixtures.
- Designed with a single notch on the frame for immediate beam angle identification.
- Compact design allows for convenient storage directly inside the fixture's charging case.
- Delivers a bright, even field of 311 lux at 5 meters with the filter installed.

### SPECIFICATIONS

#### Optical

**Beam Angle:** 18.9°

**Field Angle:** 37.3°

**Illuminance:** 311 lux @ 5 m (AC)

**Lumens:** 1254 (AC)

**Illuminance:** 125 lux @ 5 m (Battery curve off)

**Lumens:** 503 (Battery curve off)

**Illuminance:** 145 lux @ 5 m (5 hr)

**Lumens:** 588 (5 hr)

**Illuminance:** 91 lux @ 5 m (8 hr)

**Lumens:** 372 (8 hr)

**Illuminance:** 58 lux @ 5 m (12 hr)

**Lumens:** 235 (12 hr)

**Illuminance:** 37 lux @ 5 m (18 hr)

**Lumens:** 150 (18 hr)

#### Construction / Physical

**Dimensions:** 4.33 in dia. (110 mm dia)

**Weight:** 0.05 lb (0.025kg)

#### Certifications / Qualifications

**Certifications:** CE

**IP Rating:** IP65, temporary outdoor/wet use

#### What's Included

WELL POD 2 15° Filter X 6