

WELL POD 2 60° x 10° Filter Pack



A six-pack of 60 x 10° elliptical filters in magnetic frames designed to easily shape the light output of the WELL POD 2.

Perfectly suited for applications requiring a wide, linear beam spread, such as grazing walls, illuminating pathways, or highlighting long scenic elements.

- Widens the fixture's native 11.5° beam to a broad 16.3° x 46.1° elliptical wash.
- Features magnetic frames for instant, tool-free attachment to the WELL POD 2.
- Packaged as a set of six to efficiently outfit multiple WELL POD 2 fixtures.
- Includes a double notch for quick, tactile identification of the 60° x 10° filter.
- Designed with a compact profile for simple storage within the fixture's charging case.
- Provides precise optical control for shaping light into an elongated, linear beam.

SPECIFICATIONS

Optical

Beam Angle: 16.3 X 46.1°

Illuminance: 161 lux @ 5 m (AC)

Lumens: 1400 (AC)

Illuminance: 66 lux @ 5 m (Battery curve off)

Lumens: 573 (Battery curve off)

Illuminance: 77 lux @ 5 m (5 hr)

Lumens: 666 (5 hr)

Illuminance: 48 lux @ 5 m (8 hr)

Lumens: 421 (8 hr)

Illuminance: 31 lux @ 5 m (12 hr)

Lumens: 268 (12 hr)

Illuminance: 20 lux @ 5 m (18 hr)

Lumens: 170 (18 hr)

Construction / Physical

Dimensions: 4.33 in dia. (110 mm dia)

Weight: 0.05 lb (0.025kg)

Certifications / Qualifications

Certifications: CE

IP Rating: IP65, temporary outdoor/wet use

What's Included

WELL POD 2 60x10° Filter X 6