

Ovation F-95WW

FEATURES

- 16-bit dimming resolution for smooth fades
- Flat, even field of light
- Virtually silent operation for use in any situation
- Simple and complex DMX channel profiles for programming versatility
- Manually controlled variable zoom angle between 21° to 83°

SPECIFICATIONS

OPTICAL

- Light Source: 9 LEDs (WW) 10 W, (2.8 A), 100,000 hours life expectancy
- Color Temperature (at full): 3199 K
- CRI: 91
- Beam Angle: 11° to 60°
- Field Angle: 21° to 83°
- Zoom Angle: 21° to 83°
- Lumens (21°): 1,681
- Lumens (83°): 3,741
- Illuminance (21°): 1,430 lux @ 5 m
- Illuminance (83°): 133 lux @ 5 m
- PWM Frequency: 600 Hz

DYNAMIC EFFECTS

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Zoom: Manual
- Focus: Manual
- Strobe Rate: 0 to 20 Hz
- Dim Modes: 5
- Dim Curves: 4

CONSTRUCTION / PHYSICAL

- Dimensions: 12.8 x 11 x 16.5 in (325 x 279 x 420 mm)
- Weight: 13.4 lb (6.1 kg)
- Exterior Color: Black
- Gel Frame Size: 6.25 in/159 mm

CONNECTIONS

- Power Connection: Edison plug to Neutrik powerCON
- Power Input: Neutrik powerCON
- Power Output: Neutrik powerCON
- Data Connectors: 3- and 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

CONTROL

- Control Protocol: DMX
- DMX Channels: 1, 2 or 3
- Modes/Personalities: 3 personalities (UNO, DOS, STD.P)

ELECTRICAL



- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 15 units @ 120 V; 25 units @ 208 V; 28 units @ 230 V
- Power and Current: 108 W, 0.89 A @ 120 V, 60 Hz
- Power and Current: 110 W, 0.53 A @ 208 V, 60 Hz
- Power and Current: 110 W, 0.48 A @ 230 V, 50 Hz

CERTIFICATIONS / QUALIFICATIONS

- CE, MET
- IP Rating: IP20, dry location

WHAT'S INCLUDED

- Ovation F-95WW
- [Neutrik powerCON power cord](#)
- Gel frame (6.25 in/159 mm accessories)

OPTIONAL ACCESSORIES

- Professional Clamps: [CTC-50HC](#), [CTC-50HCN](#)
- [Neutrik powerCON cables](#)
- [3-pin or 5-pin DMX Cables](#)
- Color Blending Filters: DF60X1D, DF20D
- [Ovation F6.25" Barndoor](#)